The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON\97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON MAR - 71977 State Well No. 44/28k 2065

(Please type or print) TOR RESOURCES State Rermit No.

(Do not write above this line)

ALEM. COECOM

	The second secon
(1) OWNER: Name L& RU& W POLLOCK	(10) LOCATION OF WELL:  County MC Driller's well number 352
Address High Way 30 Hermiston	NW 14 NW 14 Section 20 T. LN R. 28 E W.M.
	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	SW corner
New Well □ Deepening ▼ Reconditioning □ Abandon □	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(A) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found ft.
ary Driven Domestic Industrial Municipal	Static level 26 ft. below land surface. Date Feb. 21
rig	Artesian pressure lbs. per square inch. Date
) CASING INSTALLED: Threaded Welded Welded W. J. G. " Diam. from	(12) WELL LOG: Diameter of well below casing
	Depth drilled ft. Depth of completed well ft.
	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,
) PERFORATIONS: Perforated? W Yes   No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used TOPCH	MATERIAL From To SWL
Size of perforations 1, in. by 6 in.	1 110110.1502.da-(720) KD 21
1/0 perforations from 2.7 ft. to 1.05 ft.	1111 D D 110 75 26
perforations fromft. toft.	712 RUDWA 75 100 26
perforations from ft. toft.	a la l Oyall O &
(E) (CONTENTS	Clay prou (1)
(7) SCREENS: Well screen installed?   Yes No	100 100 26
Manufacturer's Name	Brove10 110 119 26
Type         Model No.           Diam         Slot size         Set from         ft.	BUCKAR Pack
Diam. Slot size Set from ft. to ft.	10 POCK 411 POCK 110120 26
Diant	119130 12
WELL TESTS: Drawdown is amount water level is lowered below static level	
s a pump test made?  Yes No II yes, by whom?	
Id: gal./min. with ft. drawdown after hrs.	
" " "	
, , , , , , , , , , , , , , , , , , ,	
Ealer test gal./min, with ft. drawdown after hrs.	- <del>-</del>
mperature of water Depth artesian flow encountered ft.	Work started Feb 4 19 77Completed Feb 224 19 7
	Date well drilling machine moved off of well Flat 24 1977
(9) CONSTRUCTION:	Drilling Machine Operator's Certification:
Well seal—Material used	This well was constructed under my direct supervision.
Well sealed from land surface toft.  Diameter of well bore to bottom of sealin	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal	[Signed] I. R. Fredericker Date Fol 25, 19.7.
Number of sacks of cement used in well seal	(Brilling Machine Operator)
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No.
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons	
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used?   ▼ Yes □ No Plugs Size: location ft.	Name U.B. FREDEPICKSON
Did any strata contain unusable water?   Yes No	(Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address /7 / 20 / 20,66
Method of sealing strata off	[Signed] P. F. Moderlandon
Was well gravel packed? Yes   No Size of gravel: 3" 46"	(Water Well Contractor)
Gravel placed from2ft. toft.	Contractor's License No. 63.35 Date 1 16 2 19.