The original and first copy of this report are to be filed with the

Gravel placed from .

WATER WELL REPORT

7 state Well No. HN/28 = -

STATE ENGINEER, SALEM, OREGON'S E TATE OF OREGON (Please type or print) within 30 days from the date of well completion.

SFP - 5 1975 (Do not write above this line)

/	W a
	218)
	- 17214
- 1	5-4-/-

State Permit No. ..

(1) OWNER: WATER RESOURCES DEPT.	(10) LOCATION OF WELL:
Name Ronald Bake SALEM, OREGON	70
Address P.C. Bey 169	
Hermston, Oregon 97838	14 14 Section 22 T. 4 N R. 28 E. W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner
New Well Deepening Reconditioning Abandon	
If abandonment, describe material and procedure in Item 12.	
	(11) WATER LEVEL: Completed well.
Rotery W Driven D	Depth at which water was first found ft.
Cable	Static level 250 ft. below land surface. Date 8-5-7.
Dug Bored Irrigation Test Well Other	
CASING INSTALLED: Threaded I Wolded N	
"Diam. from	(12) WELL LOG: Diameter of well below casing 12"
"Diam. from ft. to ft. Gage	Depth drilled ft. Depth of completed well 3 // ft.
"Diam. from ft. to ft. Gage ft. Gage	Formation: Describe color, texture, grain size and sixuature of
	I WILL DOLOW WINCHIESS MILL HARLING OF AGON STROTHING AND ACCORDED TO
PERFORATIONS: Perforated? Yes No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
_ype of perforator used	MATERIAL
Size of perforations in. by in.	To SWL
perforations from ft. to ft.	peamed from 8" D12"
perforations from	From 251' to 311'
perforations from ft. to ft.	
/7\ CCDEENIC.	
wen acteen maraned! [] ies [] No	
Manufacturer's Name	
Type Model No Diam Slot size Set from ft. to ft.	
Diam. Slot size Set from ft. to ft.	
Dot size	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? Yes No If yes, by whom?	
Yield: gal/min with	
tt. drawdown arter hrs.	
"	
Baller test / 00 gal./min. with 50 ft. drawdown after / hrs.	
Artesian flow g.p.m.	
erature of water Depth artesian flow encountered ft.	Work started 7-29 1975 Completed 8-5-1974
(9) CONSTRUCTION:	Date well drilling machine moved off at
$h \cdot d' + u \wedge d'$	
* * * * * * * * * * * * * * * * * * * *	Drilling Machine Operator's Certification:
Well sealed from land surface toft. Diameter of well bore to bottom of seal in.	This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal in.	best knowledge and bener.
Number of sacks of cement used in well seal sacks	[Signed] (Orilling Machine Operator) Date
Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No. 665
Brand name of bentonite	
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? Yes No Plugs Size: location ft.	and belief.
Did any strata contain unusable water? Yes No	Name TROY GRIFFIN (Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address 900 HERMISTOH AVE HERMISTOH OPE
Method of sealing strata off	
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	[Signed]

Contractor's License No. 65..... Date ...