NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

STATE OF OREGON

J N I	age.	-240	à
		<u>~</u>	١

WATER RESOURCES DEPARTMENT,

SALEM, OREGON 97310 MAR 20 1980 within 30 days from the date of well completion.

(Please type or print) WATER RESOURCES DEPT No.

AUG 1 3 1980° Well No. 12

MANUAL CALANAGES DEPT	SALEM, OREGON	(2)3/
(1) OWNER: SULFUL OREGON	(10) LOCATION OF WELL:	
Name Circle "C" Farms, Inc.	County Umatilla Driller's well no	umber Ol
AddressRt. 1, Box 1961, Hermiston, Oregon	SE ¼ NE ¼ Section 24 T. 4N	R. 28E W.M.
	Bearing and distance from section or subdivisi	on corner
(2) TYPE OF WORK (check):		
New Well ☑ Deepening □ Reconditioning □ Abandon □		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.
(3) TYPE OF WELL: (4) PROPOSED USE (check):		94 ft.
y 🗷 Driven 🗆 Domestic 🗆 Industrial 🗀 Municipal 🗀	Static level 290 ft. below land s	
Jetted Irrigation Test Well Other	Artesian pressure lbs. per squar	
CASING INSTALLED: Threaded Welded	(40) TUDI I TOG	
10 " Diam. from +1 ft. to 234 ft. Gage .250	(12) WELL LOG: Diameter of well b	- · · · · · · · · · · · · · · · · · · ·
	Depth drilled 765 ft. Depth of compl	eted well 765 ft.
	Formation: Describe color, texture, grain size and show thickness and nature of each stratu	•
	with at least one entry for each change of forma	tion. Report each change in
) PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate prin	cipal water-bearing strata.
Type of perforator used	MATERIAL	From To SWL
Size of perforations in. by in.	Fine sand	0 12
perforations from ft. to ft.	Coarse sand	12 18
perforations from ft. to ft.	Cemented gravel	18 61
perforations from ft. to ft.	Coarse sand & gravel Coarse white sand	61 194 WB 1s
(7) SCREENS: Well screen installed? ☐ Yes ▼ No	Broken Brown basalt	224 230 WB
(7) SUREENS: Well screen installed? Yes No	Black basalt (med)	230 291
Type Model No.	Brown baslat (med-soft)	291 305 WB
Diam Slot size Set from ft. to ft.	Black basalt (med)	305 370
Diam Slot size Set from ft. to ft.	Porous Blk basalt w/claystone	<u> </u>
	Black basalt (med-hard)	385 519
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Gray basalt (hard)	519 540
a pump test made? Yes No If yes, by whom?	Porous black basalt	540 545 WB
viold: gal./min, with ft. drawdown after hrs.	Brown basalt	545 585
Estimated 300 GPM " "	Black basalt	585 635
" Air Test " " "	Gray basalt	635 644 659 WB
ler test gal./min. with ft. drawdown after hrs.	Porous red basalt Porous balck basalt	644 659 WB 659 752
Artesian flow g.p.m.	Porous brown basalt	752 765 WB
Imperature of water Depth artesian flow encountered ft.	2/20 80	
	Work started 2/27 19 60 Complete Date well drilling machine moved off of well	3-8 1980
(9) CONSTRUCTION:	Date wen drining machine moved out of wen	<u> </u>
Well seal—Material used Neat Cement	Drilling Machine Operator's Certification:	
Well sealed from land surface to	This well was constructed under my Materials used and information reported	
Diameter of well bore to bottom of sealin.	best knowledge and belief.	3/11/ 0-
Diameter of well bore below seal	[Signed] (Drilling Machine Operator)	Date 3/14, 19.80
Number of sacks of cement used in well seal sacks How was cement grout placed? Grout Pipe outside of	Drilling Machine Operator's License No.	1210
casing		
	Water Well Contractor's Certification: This well was drilled under my jurisd.	iction and this report is
	true to the best of my knowledge and bel	
Was a drive shoe used? Yes No Plugs Size: location ft.	Name Columbia Basin Well Di	
Did any strata contain unusable water? Yes No	(Person, firm or corporation) Address Rt. 1, Box 1961, Hermi	(Type or print) Lston, Or. 97838
Type of water? depth of strata Method of sealing strata off	Audiess	
	[Signed] (Water Well Contr	actor)
Was well gravel packed? Yes XNo Size of gravel:	Contractor's License No. 772 Date	. /
Gravel placed from ft. to ft.	Community of the state of the	 , 17.0.