NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 9/310 within 30 days from the date of well completion.

RECEIVED

UMATWATER WELL REPORT JUL 1 7 1974 State Well No. 4N/28E-2 ba

(Please type or print) STATE ENGINEER tate Permit No. 4-7381 (Do not write above this lin SALEM, OREGON

| (1) OWNER: | (10) LOCATION OF WELL: | | |
|--|--|---|--|
| Name William J. Nailbon | County Umatilla Driller's well number | | |
| Address R. 3 Box 26 A Hermiston, Ore. 97838 | 1/4 Section 2 T.4N | R. 28 E W.M. | |
| | Bearing and distance from section or subdivision | n corner | |
| (2) TYPE OF WORK (check): | | | |
| New Well Deepening Reconditioning Abandon | | | |
| If abandonment, describe material and procedure in Item 12. | (11) WATER LEVEL: Completed we | . | |
| (3) TYPE OF WELL: (4) PROPOSED USE (check): | Depth at which water was first found II3 ft. | | |
| * | | | |
| Cable Jetted Donnestic Industrial Industrial | 5 | | |
| Dug □ Bored □ Irrigation □ Test Well □ Other □ | Artesian pressure lbs. per square | : inch. Date | |
| CASING INSTALLED: Threaded Welded Welded Welded Threaded Welded Welded Threaded Case Case | (12) WELL LOG: Diameter of well be ft. Depth of comple | | |
| | | | |
| | Formation: Describe color, texture, grain size and show thickness and nature of each stratum | nd structure of materials; | |
| Diant. Itom | with at least one entry for each change of format | ion. Report each change in | |
| PERFORATIONS: Perforated? Yes No. | position of Static Water Level and indicate princ | ipal water-bearing strata. | |
| Type of perforator used | MATERIAL | From To SWL | |
| Size of perforations in, by in. | surface sandy soil | 0 4 | |
| perforations from ft. to ft. | sand brown | 4 II3 | |
| perforations from ft. to ft. | gravel | II3 II8 82 | |
| perforations from ft. to ft. | | | |
| periorations from | | | |
| (7) SCREENS: Well screen installed? ☐ Yes 🖺 No | | | |
| Manufacturer's Name | | | |
| Type Model No. | | | |
| Diam Slot size Set from ft. to ft. | · · | | |
| Diam. Slot size Set from ft. to ft. | | | |
| (8) WELL TESTS: Drawdown is amount water level is | | | |
| lowered below static lever | , | | |
| Was a pump test made? ☐ Yes ☐ No If yes, by whom? | | - | |
| gal./min. with ft. drawdown after hrs. | - y _e - 3 | | |
| n u u | | | |
| " " " | | | |
| air 30 gal./min. with ft. drawdown after hrs. | | | |
| Artesian flow g.p.m. | *1 | | |
| Inperature of water Depth artesian flow encountered ft. | Work started 7-9 1974 Complete | | |
| (a) CONCEDITORION. | Date well drilling machine moved off of well \overline{l} | 7-9 19 74 | |
| (9) CONSTRUCTION: cement | Drilling Machine Operator's Certification: | | |
| Well seal—Material used | This well was constructed under my | direct supervision. | |
| Well sealed from land surface to ft. | Materials used and information reported above are true to my best knowledge and belief. | | |
| Diameter of well bore to bottom of sealin. | | | |
| Diameter of well bore below seal in. | [Signed] (Chiling Machine Operator) Date 7-9 , 19 74 | | |
| Number of sacks of cement used in well sealsacks | Drilling Machine Operator's License No | | |
| Number of sacks of bentonite used in well seal sacks | | | |
| Brand name of bentonite | Water Well Contractor's Certification: | | |
| Number of pounds of bentonite per 100 gallons of water lbs./100 gals. | This well was drilled under my jurisdiction and this report is | | |
| Was a drive shoe used? 🏲 Yes □ No Plugs Size: location ft. | true to the best of my knowledge and belief. Name Allison Drilling Co. | | |
| Did any strata contain unusable water? Yes You | Name (Person, firm or corporation) (Type or print) | | |
| Type of water? depth of strata | Address R. 2, Box 309-C Hermiston, Ore. 97838 | | |
| Method of sealing strata off | K la Collings | | |
| Was well gravel packed? ☐ Yes 🚰 No Size of gravel: | [Signed] (Water Well Contractor) | | |
| Gravel placed from ft. to ft. | Contractor's License No Date | 7 - 9 , ₁₉ , ₇ | |
| the state of the s | | | |