NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 9731MAR 1 6 197 STATE OF OREGON within 30 days from the date of well completion.

STATE ENGINEER, SALEM, OREGON 9731MAR 1 6 197 STATE ENGINEER type or print)

SALEM. OREGON

UMAT	state Well No. 4N 28-2	
. *	State Permit No	

(1) OWNER:	(10) LOCATION OF WELL:		
Name John Morgan	County Umatilla Driller's well number		
Address U930 S.W. 4th	14 14 Section 2 T. 4H R. 28E, W.M.		
Hermiston, argon 97838	Bearing and distance from section or subdivision corner		
(2) TYPE OF WORK (check):			
New Well     Deepening □ Reconditioning □ Abandon □			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 90 ft.		
Rotary Driven Domestic Maintenal Municipal Domestic	Static level 30 ft. below land surface. Date 2-26-71		
Cable			
	Artesian pressure lbs. per square inch. Date		
(5) CASING INSTALLED: Threaded □ Welded 🖫	(12) WELL LOG: Diameter of well below casing		
S" Diam. from	Depth drilled 100 ft. Depth of completed well 100 ft.		
	Formation: Describe color, texture, grain size and structure of materials;		
ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrated,		
(6) PERFORATIONS: Perforated?   Yes   No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.		
e of perforator used	MATERIAL From To SWL		
Size of perforations in. by in.	Sand 0 98		
perforations from ft. to ft.	Scavel, Course, hound 98 100		
perforations from ft. to ft.			
perforations from ft. to ft.			
(7) SCREENS: Well screen installed?   Yes  No			
Manufacturer's Name			
Type Model No.			
Diam Slot size Set from ft. to ft.			
Diam Slot size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
Was a pump test made? Tyes No If yes, by whom?			
Yield: gal./min. with ft. drawdown after hrs.			
" " " "			
" " "			
Hailer test 600 gal./min. with 55 ft. drawdown after / hrs.			
Artesian flow g.p.m.			
Temperature of water Depth artesian flow encountered ft.	Work started 2-24 197/ Completed 2-26 197/		
CONSTRUCTION:	Date well drilling machine moved off of well 2-26 197/		
Weil seal-Material used Clmund	Drilling Machine Operator's Certification:		
Well sealed from land surface to 32 ft.	This well was constructed under my direct supervision.		
Diameter of well bore to bottom of sealin.	Materials used and information reported above are true to my best knowledge and belief.		
Diameter of well bore below seal in.			
Number of sacks of cement used in well seal 12 sacks			
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No		
Brand name of bentonite			
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:		
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Was a drive shoe used?			
Did any strata contain unusable water? ☐ Yes 💢 No	Name TROY GRIFFIN (Type or print)		
Type of water? depth of strata	Address 925 HER MISTON AVE, HER MISTON OPE		
Method of sealing strata off	Trough Haili		
Was well gravel packed? ☐ Yes 🕱 No Size of gravel:	[Signed] (Water Well Contractor)		
Gravel placed from ft. to ft.	Contractor's License No. 65 Date 3/1 , 19.7/		