WATER WELL REPORT STATE OF OREGON



RECEIVED

MAY 19 1982

State Well No. ## 44

WATER RESOURCES DEPT State Permit No. ... SALEM, OREGON

(1) OWNER:	(10) LOCATION OF WELL:
Name T.R. Simphot CO	County UMATI hh A Driller's well number
Address	SW & SE & Section 26 T. 4NR. 28E W.M.
Dity HERMISTON State ORE	Tax Lot # 2/02 Lot Blk Subdivision
(2) TYPE OF WORK (check):	Address at well location: HINKHE JUNCTION
ti i de la companya	HERMISTON ORE
New Well □ Deepening □ Reconditioning ▼ Abandon □	(11) WATER LEVEL: Completed well.
If abandonment, describe material and procedure in Item 12.	Depth at which water was first found ft.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Static level ft. below land surface. Date
Rotary Air 🗆 Driven 🗆 Domestic 🌋 Industrial 🕱 Municipal 🗆	Artesian pressure lbs. per square inch. Date
Trigation Test Well Other Thermal: Withdrawal Reinjection	(12) WELL LOG: Diameter of well below casing
(5) CASING INSTALLED: Steel Plastic Threaded Welded	Depth drilled ft. Depth of completed well ft. Formation: Describe color, texture, grain size and structure of materials; and show
	thickness and nature of each stratum and aquifer penetrated, with at least one entry
SFDiam from from ft to SF Gauge	for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
T INTEREST INTO TAKE THE TAKE.	
	MATERIAL From To SWL
10"Diam. from 5.42 ft. to 326 ft. 7 Gauge 2.50	AMENDED HOD
(6) PERFORATIONS: Perforated? ☐ Yes KNo	EXTENDED HINER WITH
Type of perforator used	
Size of perforations in. by in.	DUERHAP AND CEMENTED
ft. toft.	Ahh CASINGS AS
perforations fromft. to ft.	BEQUIRED INCHUDING LIVER
perforations from	WITH OVERHAP
(7) SCREENS: Well screen installed? Yes No	
Manufacturer's Name	
Type Model No	
Diam. Slot Size Set from ft. to ft.	
Diam. Slot Size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
·	
s a pump test made?	
=1½ld: gal/min. with ft. drawdown after hrs.	
1/ 1 11 1 11 1 1 1 1 1 1 1 1 1 1 1 1 1	
Air test gal/min. with drill stem at ft. hrs. Bailer test gal/min. with ft. drawdown after hrs.	444
tesian flow g.p.m.	
Temperature of water Depth artesian flow encountered ft.	Work started 5 - 3 19 \$2 Completed 5 - 12 1982
(9) CONSTRUCTION: Special standards: Yes X No 🗆 🔭	Date well drilling machine moved off of well 5-12 19 83
Well seal—Material used CEMENT	Drilling Machine Operator's Certification:
Well sealed from land surface to	This well was constructed under my direct supervision. Materials used
Diameter of well bore to bottom of seal in.	and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal	[Signed] Date 5-17, 1982
Number of sacks of cement used in well seal 236 sacks	Drilling Machine Operators License No.
How was cement grout placed? Pumped BAILER	Drilling Machine Operator's License No
DUMPED	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is true to
Was pump installed? Type HP Depth ft.	the best of my knowledge and belief.
Was a drive shoe used? ☐ Yes ☐ No ☐ Plugs Size: location ft.	Name OHAS, JUNGMANN DBIBLING CO.
Did any strata contain unusable water? Yes No	Address 75 2 4755TV/EW W.W.WASH
Type of Water? depth of strata	The state of the s
Method of sealing strata off	[Signed]
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	(Water Well Contractor)
Charles and the contract of th	Contractor's License No. 236 Date 5-17 , 1982