

RECEIVED

NOTICE TO WATER WELL CONTRACTOR: The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97311 within 30 days from the date of well completion.

UMAT 2576

WATER WELL REPORT

STATE OF OREGON

JAN 4 1977

State Well No. 4N/28E-27 cd

(Please type or print)

(Do not write above this line)

WATER RESOURCES DEPT. SALEM, OREGON

(1) OWNER:

Name J.R. Simplor Co. Address P.O. Box 1859 Caldwell, Idaho 83605

(2) TYPE OF WORK (check):

New Well [ ] Deepening [ ] Reconditioning [x] Abandon [ ] If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [x] Cased [ ] Driven [ ] Jetted [ ] Bored [ ]

(4) PROPOSED USE (check):

Domestic [ ] Industrial [x] Municipal [ ] Irrigation [ ] Test Well [ ] Other [ ]

CASING INSTALLED:

Threaded [ ] Welded [ ]

Diagrams for casing diameters and gages.

PERFORATIONS:

Perforated? [x] Yes [ ] No.

Type of perforator used Mills Size of perforations 1/4 in. by 3 in. 180 perforations from 186 ft. to 198 ft.

(7) SCREENS:

Well screen installed? [ ] Yes [ ] No

Manufacturer's Name, Type, Model No., Diam., Slot size, Set from.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? [ ] Yes [ ] No If yes, by whom? Yield: gal./min. with ft. drawdown after hrs. Baller test 400 gal./min. with 82 ft. drawdown after hrs. Artesian flow g.p.m. Temperature of water Depth artesian flow encountered.

(9) CONSTRUCTION:

Well seal-Material used Not disturbed Well sealed from land surface to ft. Diameter of well bore to bottom of seal in. Diameter of well bore below seal in. Number of sacks of cement used in well seal sacks Number of sacks of bentonite used in well seal sacks Brand name of bentonite Number of pounds of bentonite per 100 gallons of water lbs./100 gals. Was a drive shoe used? [ ] Yes [ ] No Plugs Size: location ft. Did any strata contain unusable water? [ ] Yes [ ] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [ ] Yes [ ] No Size of gravel: ft. Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Umatilla Driller's well number SE 1/4 S.W. 1/4 Section 27 T. 4N. R. 28E. W.M. Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found ft. Static level 118 ft. below land surface. Date 12-16-76 Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing

Depth drilled 0 ft. Depth of completed well 230 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Includes handwritten note: 'see next page water rights file U-349'

Work started 12-8 1976 Completed 12-10 1976

Date well drilling machine moved off of well 12-10 1976

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] James I. Leitch Date 12-11, 1976 (Drilling Machine Operator)

Drilling Machine Operator's License No. 665

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name TROY GRIFFIN (Person, firm or corporation) (Type or print)

Address 900 HERMISTON AVE, HERMISTON ORE.

[Signed] Troy Griffin (Water Well Contractor)

Contractor's License No. 65 Date 12-11, 1976