NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON within 30 days from the date of well completion.

UMAT 2592 KEULIVED WATER WELL REPORT STATE OF OREGON SEP 4 1973

State Well No. 4N (Please type or print) STATE ENGINEER (Do not write above this linSALEM, OREGONState Permit No. .. 6-5940

(1) OWNER:	(10) LOCATION OF WELL:			
Name Jim Wood	County Umatilla Driller's well no			
Address Rt. 1 Box 548 Hermiston, Ore.	14 14 Section 28 T. 4 N	R. 20	<u> </u>	W.M.
	Bearing and distance from section or subdivisi	on corner		
(2) TYPE OF WORK (check):		_		
New Well 📅 Deepening 🛭 Reconditioning 🖫 Abandon 🗋				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 100 ft.			
Rotary Driven Domestic Industrial Municipal	0 70 77			
Cable Jetted Industrial Ind				
bug Bored Imganon Test wen Outer	Artesian pressure lbs. per squar	e inch. L	Jate	
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well	helow essi	ng I	2
2 " Diam. from 0 ft. to 178 ft. Gage 250	Depth drilled 190 ft. Depth of compl		テヘヘ	ft.
" Diam, from ft. to ft. Gage	Formation: Describe color, texture, grain size			
	and show thickness and nature of each stratu			
DEDEOD A MIONS.	with at least one entry for each change of forma position of Static Water Level and indicate prin			
PERFORATIONS: Perforated? Ty Yes No.	-	1 1		.
Type of perforator used Mills knife	MATERIAL	From	To	SWL
Size of perforations $\frac{1}{2}$ in. by $2\frac{1}{2}$ in.	surface sand brown	10-1	42	
612 perforations from 100 ft. to 150 ft.	cement gravel	42	82_	
perforations from ft. to ft.	clay_yellow		100	
perforations from ft. to ft.	gravel		T05_	<u>-81</u>
(7) SCREENS: Well screen installed? ☐ Yes ₽ No	clay & gravel, yellow	1 1	₹ 27	1
Manufacturer's Name	yellow	127 740	I40 I50	
Type Model No.	gravel	T50	765.	*
Diam. Slot size Set from ft. to ft.	sand		T69	<u>"</u>
Diam, Slot size Set from ft. to ft.	gravel & sand	169	1.78	1
	broken rock, black	T 78	T90	,
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	_ orozen rock, orack	1-10-1	130	
Was a pump test made? ☐ Yes ☐ No If yes, by whom?				
Yield: gal./min. with ft. drawdown after hrs.				
" " "				
y " " " " " " "				
<u> </u>		 		*
Bailer test 75 gal./min. with 3 ft. drawdown after 2 hrs.		+		.
Artesian flow g.p.m.				<u> </u>
erature of water Depth artesian flow encountered ft.	Work started 8-15 1973 Complet	<u>ed 8 - 30</u>		19 73
(9) CONSTRUCTION:	Date well drilling machine moved off of well	3 - 3I		19 73
	Drilling Machine Operator's Certification:	!		
Well seal—Material used	This well was constructed under my	direct	super	vision.
Well sealed from land surface to	Materials used and information reported best knowledge and belief.	above a	re true	e to my
Diameter of well bore to bottom of sealI.6 in.		rDoto Ω (or	1077
Diameter of well bore below sealin. Number of sacks of cement used in well seal	[Signed]			
Number of sacks of bentonite used in well seal	Drilling Machine Operator's License No.	200		
Brand name of bentonite				
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:			
of waterlbs./190 gals.	This well was drilled under my jurisd		d this	report is
Was a drive shoe used? ♀ Yes □ No Plugs Size: location ft.	true to the best of my knowledge and be Name Allison Drilling Co.	ucz.		
Did any strata contain unusable water? Yes NO	Name A11150n DF11111B CO. (Person, firm or corporation)	(T y	pe or pri	int)
Type of water? depth of strata	Address RR. 2Box 309-0 Hermi	ston	07-8	97838.
Method of sealing strata off		In	• • •	- · - /-
	[Signed] (Water Well Cont	ractor)		
	· · ·	-3I		10 73
Gravel placed from ft. to ft.	The Contractor of Enterior IVI,			40