

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

UMAT 2603

STATE OF OREGON WATER WELL REPORT

STATE OF OREGON

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED JUL 11 1967 STATE ENGINEER OREGON

(Please type or print) G-3688 also G-4135

State Well No. 4N/28-30R State Permit No. UMAT 2603

(1) OWNER: Assigne G. Picison Prunedood Rancher

Name NORMAN ANDERSON Address HERMISTON, OREGON

(2) TYPE OF WORK (check):

New Well [x] Deepening [ ] Reconditioning [ ] Abandon [ ] If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL: (4) PROPOSED USE (check):

Rotary [ ] Driven [ ] Cable [x] Jetted [ ] Domestic [ ] Industrial [ ] Municipal [ ] Dug [ ] Bored [ ] Irrigation [x] Test Well [ ] Other [ ]

CASING INSTALLED: 16" Diam. from 0 ft. to 100 ft. Gage 250.44

PERFORATIONS: Perforated? [x] Yes [ ] No. Type of perforator used HILLS Size of perforations 1/4 in. by 3 in. 50 perforations from 32 ft. to 57 ft.

(7) SCREENS: Well screen installed? [ ] Yes [x] No Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well. Level 132 ft. below land surface Date Artesian pressure lbs. per square inch Date

(9) WELL TESTS: Drawdown is amount water level is lowered below static level Was a pump test made? [x] Yes [ ] No If yes, by whom? LANE 2020 gal./min. with 31 ft. drawdown after 6 hrs.

Bailer test gal./min. with ft. drawdown after hrs. Artesian flow g.p.m. Date Temperature of water 68 Was a chemical analysis made? [ ] Yes [x] No

(10) CONSTRUCTION: Well seal—Material used Bentonite Depth of seal 20' Diameter of well bore to bottom of seal 20 in. Were any loose strata cemented off? [ ] Yes [x] No Depth Was a drive shoe used? [x] Yes [ ] No Did any strata contain unusable water? [ ] Yes [x] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [ ] Yes [x] No Size of gravel: Gravel placed from ft. to ft.

(11) LOCATION OF WELL:

County Yamhill Driller's well number SE 1/4 SE 1/4 Section 30 T4N R28 E of W.M. Bearing and distance from section or subdivision corner 600' east of West line 200' N. of South line

(12) WELL LOG: Diameter of well below casing 12" to 300' Depth drilled 8'-300'-721 ft. Depth of completed well 721 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with columns: MATERIAL, From, To, SWL. Rows include Sand & Gravel, Blue Clay, Sand, Clay w/ Imbedded Gravel, Basalt, Dense Basalt, Blue Clay, Med Hard Basalt, Dense Basalt, Red Breccia, Dense Basalt, Med. Hard Basalt, DENSE BASALT, URSEVIAN BASALT, HIGHLY WATER BEARING.

Work started DEC 15 1966 Completed 6-28 1967 Date well drilling machine moved off of well 7-3 1967

Drilling Machine Operator's Certification: This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. [Signed] John D. ... Date ... 19... Drilling Machine Operator's License No. 252

Water Well Contractor's Certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. NAME W.R. F.I.R. Drilling Co. Address 3401 NE 130 ave Portland [Signed] S.P.R. ... (Water Well Contractor) Contractor's License No. 405 Date 7-8 1967