NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER WELL REPORT CEIVED

STATE OF OREGON MAR 281977 State Well No. 4N 28E-33

STATE ENGINEER, SALEM, OREGON 97310 WIA T within 30 days from the date of well completion.

(Do not write above the ATER RESOURCES SDEPTermit No. SALEM, OREGON

1) OWNER:	(10) LOCATION OF WELL:		
Vame Woodrow Walker	County Umatilla Driller's well number		
Address R. I Box 234 Hermiston, Ore. 97838	4 Section 33 T. 4N	R. 28E	<u> </u>
a) myne or work (1, 1).	Bearing and distance from section or subdivision	on corner	
2) TYPE OF WORK (check):			
New Well Abandon	·		
f abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.	
3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 60		ft.
tary Driven Domestic Industrial Municipal	Static level 22 ft. below land s	urface. Date	3-24-77
e ☐ Jetted ☐ ☐ Irrigation ☐ Test Well ☐ Other ☐	Artesian pressure lbs. per squar		
CASING INSTALLED: Office to the second of t	(12) WELL LOG: Depth drilled II3 ft. Depth of completed well II3 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.		
Type of perforator used torch	MATERIAL	From T	o swl
Size of perforations in. by 2 in.	surface sandy soil	0 3	
96 perforations from 40 ft. to 60 ft.	gravel	3 <u>I</u>	5
perforations from ft. to ft.	clay yellow	I5 5	5
perforations from ft. to ft.	broken rock	55 79	9
a. conserio	clay yellow	79 I	10
7) SCREENS: Well screen installed? Yes No	gravel	IIO II	3 22
Manufacturer's Name		 	
Type			
Diam. Slot size Set from ft. to ft.			
Jan. Stot Size Size See Iron			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
a pump test made? Tyes No If yes, by whom?			
gal./min. with ft. drawdown after hrs.			
, , , , , , , , , , , , , , , , , , , ,			
" " "		 	
er test 75 gal./min. with 60 ft. drawdown after 2 hrs.			- -
<u> </u>		 	
tesian flow g.p.m.	Week standed 3-23-77 10 Complete	3- 1±2	24 19 77
mperature of water Depth artesian flow encountered ft.	work started 19 Complete	<u></u>	
(9) CONSTRUCTION:	Date well drilling machine moved off of well		
Well seal—Material used	Drilling Machine Operator's Certification: This well was constructed under my Materials used and information reported best knowledge and belief.	direct su	pervision. true to my
Diameter of well bore below sealin.	[Signed]	Date3-2	57.7 19
Number of sacks of cement used in well sealsacks	Drilling Machine Operator) 484 Drilling Machine Operator's License No.		
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No.		
Brand name of bentonite	Water Well Contractor's Certification:		
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is		
of waterlbs./100 gals.	true to the best of my knowledge and belief.		
Was a drive shoe used? A yes D No Plugs Size: location ft.	Name Allison Drilling Co. (Person, firm or corporation) (Type or print)		
Did any strata contain unusable water? Yes No	R. 2 Box 2286 Hermiston, Ore. 97838		
Type of water? depth of strata	Address R O OOD		
Method of sealing strata off	[Signed] (Water Well Contractor)		
Was well gravel packed? Tyes No Size of gravel:			10
Gravel placed from ft. to ft.	Contractor's License No. 419 Date3	-25-77	, 19