NOTICE TO WATER WELL CONTRACTOR The original and first copy

of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT GETVED

STATE OF OREGON FEB231977 State W

(Please type or print) RESOURCES State Permit No.
(Do not write above this line) RESOURCES DEPT.

			#				
		41.1	/_	1.1		11	
7611	Nο	411	12	4E	6	Dh	
A CIT	110.	7	· · · · · · · · · · · · · · · · · · ·			····· "\$	٠.

(1) OWNER: Name Chip Leanard Bedord.	(10) LOCATION OF WELL:	s • ·	14
Name	County Umatilla Driller's well nu		
Address Rout 3 Box 3954 Hermioton Ore 97838	Nw 14 nw 14 Section 6 T. 14 Bearing and distance from section or subdivision		<u> W.M.</u>
(2) TYPE OF WORK (check):	5%: from Punkin cente		r centrl
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐	2 Acres tax lot	24 100 1100	_ OOMOL _
If abandonment, describe material and procedure in Item 12.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed w	en.	
	Depth at which water was first found 45!		ft.
Cable Jetted Jetted Industrial Industrial	Static level 35 ft. below land s	urface. Date 2	99.7 7.
I Bored I Irrigation Test Well Other	Artesian pressure lbs. per square	e inch. Date	
(5) CASING INSTALLED: Threaded Welded 4.	(12) WELL LOG: Diameter of well b		
" Diam. from ft. to ft. Gage	Depth drilled 90 ft. Depth of comple	eted well 87	ft.
"Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size a		
The state of the s	and show thickness and nature of each stratum with at least one entry for each change of format		
(6) PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate princ		
Type of perforator used	MATERIAL	From To	SWL
Size of perforations in. by in.	Rupert Sand browntop soi	L 0 10	- i
perforations fromft. toft.	Grey sand and clay	10 20	
perforations fromft. toft.	course grey sand	20 40	
perforations fromft. toft.	capilary water grey sand	40 50	-
periorations from	quick sand fine clay grey	50 80	
(7) SCREENS: Well screen installed? Yes No	water gravel pez size	80 90	
Manufacturer's Name			-35- "
Type Model No.			
Diam Slot size Set from ft. to ft.			
Diam. Slot size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			-
a pump test made? Tyes 15 No If yes, by whom? blow	•		
d: 100 gal./min. with 30 ft. drawdown after 6 hrs.			
" " " "	7 T		
	And a second sec		
" " " " " " " " " " " " " " " " " " "	- Constitution of the Cons		
Per test gal./min. with ft. drawdown after hrs.	: £.:		
isian flow g.p.m.			
Temperature of water 1 Depth artesian flow encountered ft.	Work started Feb 7 19 77 Complete	ed feb 8	19 77
(9) CONSTRUCTION:	Date well drilling machine moved off of well	Feb 9	19 77
D	Drilling Machine Operator's Certification:	. 100	
	This well was constructed under my	direct super	vision.
Well sealed from land surface to50ft. Diameter of well bore to bottom of sealfn.	Materials used and information reported	above are true	to my
Diameter of well bore to bottom of seal	best knowledge and belief.	Febl5	77
3/	[Signed] (Drilling Machine Operator)	Date	., 19' '
8	Drilling Machine Operator's License No	539	
Brand name of bentonite			·*
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:		
of waterlbs./100 gals.	This well was drilled under my jurisdi		eport is
Was a drive shoe used? Yes No Plugs Size: location ft.	true to the best of my knowledge and beli		
Did any strata contain unusable water? Yes No	Name Great Western Drilling Co (Person, firm or corporation)	O (Type or prir	 nt)
	Address P.0 box 349 Hermiston,		
	(,)(10 ())		
Method of sealing strata off	[Signed]	zeenai	
Was well gravel packed? ☐ Yes ⅓ No Size of gravel:	Water Well Control	eb 15	77
Gravel placed from	Contractor's License No. Date		19