NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

(Please type or print)

(Do not write above this line)

1MAT)	State Well No. 1N/32E -9dc
	State Permit No.

Control of the Contro			
(1) OWNER:	(10) LOCATION OF WELL:		
Name John BOTTS	County Umatila Driller's well number		
Address Rt2 Box 1/6 CC	SW4 SE4 Section 9 T. 17 R. 30 W.M.		
PRODUCTON Chay 97/61	Bearing and distance from section or subdivision corner		
(2) TYPE OF WORK (check): /			
New Well Deepening Reconditioning Abandon Abandon ■			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 276 ft.		
Rotary Driven Domestic Industrial Municipal Domestic Industrial Municipal	Static level O ft. below land surface. Date 9-21-7		
☐ Bored ☐ Irrigation ☐ Test Well ☐ Other ☐	Artesian pressure /O lbs. per square inch. Date 7-2/20		
(5) CASING INSTALLED: Threaded Welded 250	(12) WELL LOG: Diameter of well below casing Depth drilled 300 ft. Depth of completed well 500 ft.		
"Diam. from	Formation: Describe color, texture, grain size and structure of materials:		
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in		
(6) PERFORATIONS: Perforated? Yes D.No.	position of Static Water Level and indicate principal water-bearing strata.		
Type of perforator used	MATERIAL From To SWL		
Size of perforations in. by in.	Soil O 6		
perforations from ft. to ft.	gravel 68		
perforations from ft. to ft.	Brown basalt 8 50		
perforations from ft. to ft.	Black Baselt + yellow TAle 50 60		
(7) SCREENS: Well screen installed? Yes Yes	Block & Red Borally 180 200		
Manufacturer's Name	Black Red Garalle 180 200		
Type Model No.	Brown Bosall 274 295 0		
Diam. Slot size Set from ft. to ft.	B/Ah Bosall 295 300		
Diam. Slot size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
Was a pump test made? Yes No If yes, by whom?			
d: \$200 gal./min, with 200ft. drawdown after hrs.	La de la Caración de		
H	1000 = 10		
" " " " " " " " " " " " " " " " " " "	WATER RESOURCES DEPT		
Bailer test gal./min. with ft. drawdown after hrs.	SALEM. OREGON		
esian flow g.p.m.			
Temperature of water 6 Depth artesian flow encountered ft.	Work started Sent 14 19 Completed Sent 20 1978		
(9) CONSTRUCTION:	Date well drilling machine moved off of well Sent 2/ 1979		
Well seal-Material used fort and Comet	Drilling Machine Operator's Certification:		
Well sealed from land surface to 18ft.	This well was constructed under my direct supervision.		
Diameter of well bore to bottom of sealin.	Materials used and information reported above are true to my best knowledge and belief		
Diameter of well bore below seal	reimodi (XAVIII) Sent 34, 78		
Number of sacks of cement used in well seal	(Drilling Machine Operator)		
How was cement grout placed?	Drilling Machine Operator's License No		
	Water Well Contractor's Certification:		
	This well was drilled under my jurisdiction and this report is		
Was a drive shoe used? Yes No Plugs Size; location ft.	true to the best of my knowledge and belief.		
Did any strata contain unusable water? Yes No	Name (Person firm or corporation) (Type or print)		
Type of water? depth of strata	Address Kt 1 Box 14 116T Lock, Oney 9216		
Method of sealing strata off	[Simod] Sall His		
Was well gravel packed? 🗌 Yes 🗎 No 🥏 Size of gravel:	[Signed] (Water Well Contractor)		
Gravel placed from ft. to ft.	Contractor's License No. 739 Date 9-24 , 1979		
(HER ADDITIONAL SHEETS IN NECESSARY)			