NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

## WATER WELL REPORT

## STATE OF OREGON

(Please type or print)

(Do not write above this line)

UM 1 T 2819

State Well No.  $\frac{4n/29\varepsilon-100}{2}$ 

State Permit No. ....

(1) OWNER:	(10) LOCATION OF WELL:
Name John C. Quick	
Address Rt. 180x 1263 Stanfield	SiV 4 NE 4 Section / T. 4/1/ P. 20 E
-Dregon 97875	1. // R. 27 L W.M.
(2) TYPE OF WORK (check):	Aprox. 900 North & 950' Fast v1
New Well 🗹 Deepening 🗌 Reconditioning 🗍 Abandon 🖸	the SIN Com of MEN Contract
If abandonment, describe material and procedure in Item 12.	7 - 7 - 7 - 7 - 7 - 7 - 7 - 7 - 7 - 7 -
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.
Rotary Driven Domestic Dindustrial Municipal Domestic	Depth at which water was first found 68, 4  Static level 60 5 ft below lond with 5 Mars 50
Des Bored I Irrigation A Test Well Dother	11. below land surface. Date /144/5/8
	Artesian pressure NONE lbs. per square inch. Date Man S
(5) CASING INSTALLED: Threaded Welded W	(12) WELL LOG: Diameter of well below with
"Diam. from 72.2 ft. to 158.8 ft. Gage 250	Diameter of well below casing
"Diam from ft. to ft. Gage	11.
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each show.
(6) PERFORATIONS: Perforated?   Yes No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL
Size of perforations 2 in. by 2 in.	Sindy Silt Ton Spil O.C. C.S
perforations from	Silt 14 Tan 10 1 1 0 1 10 10
perforations from ft. to ft.	Brown Clay & Sand Seams 68: 120: 680
perforations from ft. to ft.	Course white sand and 120:
(7) SCREENS: Well screen installed T. V.	Brown Clay 1430
Manufacturer's Name Well screen installed? Yes Y No	Brown Clay 143:21520
Type Model No.	Drown vis Cil far hosalt 1522 176. 60.0
Diam. Slot size Set from ft. to ft.	Hard Gray Basalt 1765 219: 1
Diam. Slot size Set from ft. to ft.	Prochured brown Boselt 219.0245.
	Blue Basa 14 245 2865
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	VISCULAR 1805011 2989210 100
a pump test made?  Yes X No If yes, by whom?	VISCUTOR 13950 (4 298, 3/0, 60.5
Yield: 250 gal. bin. with 100 ft. drawdown after 1/2 hrs.	
# ##	7 6 日 日 1 日 1 日 1 日 1 日 1 日 1 日 1 日 1 日 1
" " " " " " " " " " " " " " " " " " "	mat 2 786 i
er test 2 gal./min. with 2 ft. drawdown after 2 hrs.	WATER SEA
Artesian flow NONE g.p.m.	SALESI. OFFICE
Temperature of water 55 Depth artesian flow encountered NCNEft.	
(9) CONSTRUCTION:	1930 Completed 14 224 7.3 1930
	Date well drilling machine moved off of well May 15 1980
Well seal-Material used Cement Grout Well sealed from land surface to	Drilling Machine Operator's Certification:
Diameter of well bore to bottom of seal 123/4 ormore ft.	This well was constructed under my direct supervision.  Materials used and information reported above are true to my
Diameter of well bore below seal 9/2 in Drive Shee	best knowledge and belief.
Number of sacks of cement used in well seal 22 sacks	[Signed] Date Date 1980, 1980
How was cement group placed? Transpied great	Drilling Machine Operator's License No.
Mto Anni Hrspace, Pulled 12"	
inface casing and filled Amular	Water Well Contractor's Certification:
Was a drive of the control of the co	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? ▼ Yes □ No Plugs Size: location ft.	true to the best of my knowledge and belief.  Name From Arouse Drilliage Company
Did any strata contain unusable water?   Yes No	(Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address L.O. Box 124, Hermiston, Argoon
Method of sealing strata off	[Signed John I Brown 97838
Was well gravel packed? [] Yes No Size of gravel:	(Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 516 Date May 17 1980