NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON MAR 1.2 1976 State Well No.

(Please type or print)
WETER KESOURCES BEETPermit No.
(Do not write above this line)
SALEM, OREGON

(1) OWNER:	(10) LOCATION OF WELL:			
Name Glenn Chowning	County Umatilla Driller's well n	umber		
Address R. I Box I4I Stanfield, Ore. 97875	14 14 Section 19 T. 4N	R. 29		W.M.
	Bearing and distance from section or subdivis:	****		*******
(2) TYPE OF WORK (check):	Bearing and distance from section of subdivis.	ion comer		· · · · · · · · · · · · · · · · · · ·
New Well ♣ Deepening ☐ Reconditioning ☐ Abandon ☐			-	- ,
If abandonment, describe material and procedure in Item 12.	(11) *** A MYDD * TYYDY G . I . I			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed w	7ell.		
Rotary Driven Demostic Dandstold Demostic	Depui at which water was first round			ft.
Cable	Static level 45 ft. below land	surface. I	Date 3-2	<u>2~76 </u>
Dug □ Bored □ Irrigation X□ Test Well □ Other □	Artesian pressure lbs. per squa	re inch. I	Date	
CASING INSTALLED: 8 "Diam from 0 ft to 105 ft Gage 250 ft Gage 25	(12) WELL LOG: Diameter of well Depth drilled 130 ft. Depth of comp	leted well	130	ft.
PERFORATIONS: Perforated? Yes No.	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.			
Type of perforator used torch	MATERIAL	From	то	swL
Size of perforations 1/8 in. by 3 in.	Surface sand brown	0	IO	4*
124 perforations from 84 ft. to 104 ft.	clay yellow	IO	80	
perforations from ft. to ft.	gravel	80	105	43
perforations from ft. to ft.	clay with gravel	105	130	43
(7) SCREENS: Well screen installed? ☐ Yes ☐ No				
Manufacturer's Name				
Type Model No				
Diam Slot size Set from ft. to ft.				
Diam Slot size Set from ft. to ft.				
(8) WELL TESTS: Drawdown is amount water level is lowered below static level				
Was a pump test made? ☐ Yes \$\ \bar{\star}\\$ No If yes, by whom?				
Yield: gal./min. with ft. drawdown after hrs.				
" " " "				
<u> </u>				
Bailer test 300 gal./min. with 50 ft. drawdown after 2 hrs.	Next this			
Artesian flow g.p.m.				
perature of water Depth artesian flow encountered ft.	Work started 3-I 19 76 Complet	ted 3-2		19 76
(9) CONSTRUCTION:	Date well drilling machine moved off of well	3 - 2		19 76
Well seal—Material used cement	Drilling Machine Operator's Certification:	:		
Well sealed from land surface to	This well was constructed under my			
Diameter of well bore to bottom of seal	Materials used and information reported best knowledge and belief.	above a	ire true	to my
Diameter of well bore below seal	[Signed] Tile. alling	Date 3-4	5	10 76
Number of sacks of cement used in well seal	(Drilling Machine Operator)	700		., 10
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No. 300			
Brand name of bentonite	Walter Will Co. 1	· · · · · · · · · · · · · · · · · · ·	-	
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:			
of water lbs./100 gals.	This well was drilled under my jurisd true to the best of my knowledge and be		d this r	eport is
Was a drive shoe used? Yes No Plugs Size: location ft.	Name Allison Drilling Co.	MCT.		
Did any strata contain unusable water? 🗌 Yes 💆 No	(Person, firm or corporation)		pe or prin	
Type of water? depth of strata	Address R. 2 Box 2286 Hermi ston	, Ore.	97838	3
Method of sealing strata off	R 1. 1200:	A		
Was well gravel packed? Yes No Size of gravel:	[Signed] (Water Well Cont	ractor)		
Cravel placed from	Contractor's License No 419 Date 5-			10 7