NOTICE TO WATER WELL CONTRACTOR The original and first copy
of this report are to be
filed with the

WATER WELL REPORT CEIVEL

STATE OF OREGONAUG2 9 1974

State Well No. 4N 29E-25

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

(Please type or print) TATE ENGINEER
(Do not write above this line) SALEM, OREGON

| State Permi | t No. | |
|-------------|-------|--|

| (1) OWNER: | (10) LOCATION OF WELL: | | |
|--|--|--------------------------|---------------------------------------|
| Name Verry Waters | County Umatilla Driller's well number | | |
| Address (RT BH 66 | 14 14 Section 25 T. 47. R. 298. W.M. | | |
| Stanfield, Oregon 17875 | Bearing and distance from section or subdivision corner | | |
| (2) TYPE OF WORK (check): | Dearing and distance from section of subdivisi | on comer | |
| New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐ | | | · · · · · · · · · · · · · · · · · · · |
| If abandonment, describe material and procedure in Item 12. | (11) THATTED TEXTED (C | _ 11 | |
| (3) TYPE OF WELL: (4) PROPOSED USE (check): | (11) WATER LEVEL: Completed w | en. | |
| notice for notice of | Depth at which water was first found 89 | | ft. |
| Cable | Static level 80 ft. below land s | surface. Date ${\cal S}$ | ·20-74 |
| Dug Bored I Irrigation Test Well Other | Artesian pressure lbs. per squar | e inch. Date | |
| CASING INSTALLED: Threaded Welded 5. | (12) WELL LOG: Diameter of well h | pelow casing | / // |
| "Diam from ft to ft Gage | Depth drilled 200 ft. Depth of compl | eted well Zo | Oft. |
| "Diam. from ft. to ft. Gage | Formation: Describe color, texture, grain size a | | |
| Diant. 11011 | and show thickness and nature of each stratur with at least one entry for each change of format | | |
| PERFORATIONS: Perforated? Yes No. | position of Static Water Level and indicate prin | | |
| Type of perforator used | MATERIAL | From To | SWL |
| Size of perforations in. by in. | Tonsoil - | 0 5 | |
| | Show 0 + Clanstone | 5 20 | |
| perforations from ft. to ft. | Dich hache have | 20 30 | |
| - | Rack light have | 30 42 | <u> </u> |
| perforations from ft. to ft. | Basaer | 42 57 | |
| (7) SCREENS: Well screen installed? Yes No | Park light drawns | 57 63 | |
| Manufacturer's Name | Ruh had | 63 71 | |
| Type Model No | Baselt | 71 89 | - |
| Diam Slot size Set from ft. to ft. | Rock hed | 89 102 | W.B. |
| Diam Slot size Set from ft. to ft. | Rack light brown | 102 106 | W 123. |
| (O) YEAR Y PROGRAM Dronder in an article in the control of the con | Basaly | 106 124 | |
| (8) WELL TESTS: Drawdown is amount water level is lowered below static level | Rock light brown | 15 1 155 | in B. |
| Was a pump test made? ☐ Yes 🛣 No If yes, by whom? | Rock med. black | 133 151 | |
| Yield: gal./min. with ft. drawdown after hrs, | Rock, dark brown | 151 159 | w.B. |
| " " " | Rock, med., black | 1.59 173 | |
| " " " " | Rock, light brown | 173 182 | W.B. |
| A.L. | Basalr | 182 200 | |
| tailer-test 50 gal./min. with 95 ft. drawdown after / hrs. | | | |
| Artesian flow g.p.m. | | | |
| emperature of water Depth artesian flow encountered ft. | Work started 8-20 197 4 Complete | ed 8-20 | 1974 |
| (9) CONSTRUCTION: | Date well drilling machine moved off of well | 8-20 | 19 74 |
| | Duilling Machine Operator's Contitionion | | - |
| Well seal—Material used Cennent | Drilling Machine Operator's Certification: This well was constructed under my | direct suner | vision |
| Well sealed from land surface to 40 ft. Diameter of well bore to bottom of seal 9 in. | Materials used and information reported | | |
| | best knowledge and belief. | 6-21 | 71/ |
| Diameter of well bore below seal in. | [Signed] (Drilling Machine Operator) | Date 3 -2/ | , 19.7 4 |
| Number of sacks of cement used in well seal sacks | Drilling Machine Operator's License No | 465 | |
| Number of sacks of bentonite used in well seal sacks | | | |
| Brand name of bentonite | Water Well Contractor's Certification: | | |
| Number of pounds of bentonite per 100 gallons of waterlbs./100 gals. | This well was drilled under my jurisdi | | eport is |
| Was a drive shoe used? ★ Yes □ No Plugs Size: location ft. | true to the best of my knowledge and beli | ief. | _ |
| Did any strata contain unusable water? Yes No | Name TROY GR /FF / H (Person, firm or corporation) | (Type or pri | nt) |
| Type of water? depth of strata | Address 900 HERMISTON AVE. | F A .7 - | ••••••• |
| Method of sealing strata off | [Signed] Tray Hory | lfin. | |
| Was well gravel packed? ☐ Yes ☑ No Size of gravel: | [Signed] (Water Well Contra | actor) | ············ |
| Gravel placed from ft. to ft. | Contractor's License No | 8-21 | 1974 |
| /YYAY A SA | The state of the s | | , |