## File Original and First Copy with the STATE ENGINEER

## STATE EMGINEED

State Well No. ..

SALEM, OREGON	F OREGON State Permit No. G-1293
(1) OWNER:	(11) WELL TESTS: Drawdown is amount water level is lowered below static level on the
Name Byron & Gladys Crum, husband & wife	Was a pump test made? I Yes \( \text{In No If yes, by whom?} \)
Address Stanfield, Oregon	Yield: 400 gal./min. with 5 ft. drawdown after 4 hrs.
	" " "
(2) LOCATION OF WELL:	27 27 27 27 27 27 27 27 27 27 27 27 27 2
County Umatilla Owner's number, if any-	Bailer test gal./min. with ft. drawdown after hrs.
NW 1/4 SW 1/4 Section 31 T. 4N R.29 E W.M.	Artesian flow g.p.m. Date
Bearing and distance from section or subdivision corner	Temperature of water Was a chemical analysis made?   Yes   No
N 49° 33 56" E 2,369.4 feet from	(12) WELL LOG: Diameter of well #8 in inches.
Southwest Corner of Section 31. T4N.	Depth drilled 1 2 0 ft. Depth of completed well 2 6 ft.
Range 29 EWM in Umatilla County	Formation: Describe by color, character size of material and structure, and show thickness of aquifers and the kind and nature of the material in each
	show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.
(3) TYPE OF WORK (check):	
New Well   Deepening   Reconditioning   Abandon   Abandon	I the well grown day
If abandonment, describe material and procedure in Item 11.	the same and the same
	and the second second
PROPOSED USE (check): (5) TYPE OF WELL:	1. Dead of Park 18.
Domestic ☐ Industrial ☐ Municipal ☐ Rotary ☐ Driven ☐ Cable ☐ Jetted ☐	ALOD THE STATE OF
Irrigation ☑ Test Well □ Other □ Cable □ Jetted □ Dug ☑ Bored □	and white and
(6) CASING INSTALLED. Cement 7H dram	unall the The
(5) SILVIII OF INCLUDE: IMPORTED   WESTERN	moved he a litter
"Diam, from	hale were dulled
"Diam. from	endo The bed with
"Diam. from	and shows of known a
(7) PERFORATIONS: Perforated?   Yes No	invelled and be
Type of perforator used	these with a wood
SIZE of perforations in. by in.	flow or water se-
perforations from ft. to ft.	wester the work
perforations from ft. to ft.	was asserted ty,
ft. to ft.	Brank Wester out
perforations fromft. toft.	The soul at the
perforations from ft. to ft.	Line we flythased
(8) SCREENS: Well screen installed ☐ Yes 🛱 No	My condition well
(8) SCREENS: Well screen installed ☐ Yes 🛱 No Manufacturer's Name	the mot the time at
TypeModel No.	Let Proper 14 1 1 100
Picm Slot size Set from ft. to ft.	Con use hund it But!
Slot size Set from ft, to ft.	Work started seconds to 1957 Completed Oct 3/ 1960
(A) CONTEMPARATION	Work started Application of Completed (107 , 3 / 195
(9) CONSTRUCTION:	(13) PUMP:
Was well gravel packed?  Yes  No Size of gravel:	Manufacturer's Name Meury
Gravel placed fromft. toft. 2 lb	Type: Centrifugal 0 H.P. 15
Was a surface seal provided? Yes \( \sum \text{No To what depth? } \frac{1}{2} \) ft.  Material used in seal—	
Did any strata contain unusable water?   Yes No No	Well Driller's Statement:
Type of water? Net A Depth of strata	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Method of sealing strata off	
	NAME Shockman Bros. by
(10) WATER LEVELS:	(Person, firm, or corporation) (Type or print)
Static level / D A ft. below land surface Date	Address Hermiston, Oregon
Artesian pressure   lbs. per square inch Date	Driller's well number
Log Accepted by:	
	[Signed](Well Driller)
[Signed]	License No
· · · · · · · · · · · · · · · · · · ·	2100 210 19 Date