

STATE ENGINEER  
Salem, Oregon

UMAT  
2952

# Well Record

STATE WELL NO. 4N/29-31E  
COUNTY Umatilla  
APPLICATION NO. GR-3899

OWNER: Rose Alice Hossier

MAILING  
ADDRESS:

Route 1, Box 89

LOCATION OF WELL: Owner's No. \_\_\_\_\_

CITY AND  
STATE:

Stanfield, Oregon

SW 1/4 NW 1/4 Sec. 31 T. 4 N. S., R. 29 E. W., W.M.

Bearing and distance from section or subdivision

corner 43' S. & 137' W. of NE Cor. Sec. 31

X			

Section 31

Altitude at well \_\_\_\_\_

TYPE OF WELL: Dug & Driven Constructed 7/1/18

Depth drilled 35 feet Depth cased \_\_\_\_\_

### CASING RECORD:

Well dug to a depth of 12'. Then a 6" hole drilled to a depth of 25', then a 2" galvanized pipe was driven to a depth of 35' and the previously welded point opened with a 1/4th stick of dynamite. After 30 minutes of pumping well tested 50 gpm when pumped with "3 Byran Jackson pump, driven by 5 hp gas engine for several hours.

### FINISH:

### AQUIFERS:

### WATER LEVEL:

22 inch below surface

PUMPING EQUIPMENT: Type Myers Bulldozer

H.P. 5

Capacity 50 G.P.M.

### WELL TESTS:

Drawdown 6 ft. after \_\_\_\_\_ hours 50 G.P.M.

Drawdown \_\_\_\_\_ ft. after \_\_\_\_\_ hours \_\_\_\_\_ G.P.M.

USE OF WATER Irrigation

Temp. \_\_\_\_\_ °F.

, 19\_\_\_\_

SOURCE OF INFORMATION Well Registration Statement Cert. # GR-3542

DRILLER or DIGGER \_\_\_\_\_

### ADDITIONAL DATA:

Log \_\_\_\_\_ Water Level Measurements \_\_\_\_\_ Chemical Analysis \_\_\_\_\_ Aquifer Test \_\_\_\_\_

### REMARKS: Log

Sandy topsoil (volcanic ash)  
Hardpan (workable without pickaxe)  
Sandy subsoil  
Quicksand  
River washed gravel

Thickness	Depth to Bottom
4	4
1	5
20	25
4	29
6	35