

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

WATER WELL REPORT

RECEIVED

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

UMAT
2967

STATE OF OREGON
(Please type or print)

NOV 12 1974

State Well No. 4N/29E-32

STATE ENGINEER
SALEM, OREGON

State Permit No.

(1) OWNER:

Name Del Harmon
Address P. O. Box 252 Stanfield, Ore.

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED:

Threaded Welded

" Diam. from 10 1/2 ft. to ft. Gage
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? Yes No.

Type of perforator used

Size of perforations	in.	by	in.
perforations from		ft. to	ft.
perforations from		ft. to	ft.
perforations from		ft. to	ft.

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? Yes No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test 60 gal./min. with none ft. drawdown after 2 hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used none
Well sealed from land surface to ft.
Diameter of well bore to bottom of seal in.
Diameter of well bore below seal in.
Number of sacks of cement used in well seal sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Umatilla Driller's well number
1/4 1/4 Section 32 T. 4N R. 29 W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

more

Depth at which water was first found don't think I got any.
Static level 30 ft. below land surface. Date 10-29-74
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 8 to 10 to 14 3/4

Depth drilled 70 ft. Depth of completed well 200 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
rock grey hard	130	142	30
sand black	142	143	30-
rock grey hard	143	160	30
rock black med.	160	168	30
rock grey boldres	168	194	30
rock black med.	194	197	30
rock grey hard	197	200	30

Work started 10-3 19 74 Completed 10-29 19 74

Date well drilling machine moved off of well 10-30 19 74

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] K. L. Allison Date 10-30, 19 74
(Drilling Machine Operator)

Drilling Machine Operator's License No. 300

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Allison Drilling Co. (Person, firm or corporation) (Type or print)

Address R. 2 Box 309-0 Hermiston, Ore. 97838

[Signed] K. L. Allison (Water Well Contractor)

Contractor's License No. 419 Date 10-30, 19 74