NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report. WATER WELL	LREPORT	<i>सू</i> स
are to be fried with the	2330 - The state of the state o	4NIZOE-21/2/
WATER RESOURCES DEPARTMENT. SALEM, OREGON 97310 WAR- 2-1978 (Please type		The state of the s
Within 50 days from the date	State Permit N	I IN A K T
THE STATE OF THE S	WATER RESOURCES DEET	UNIAI
(1) OWNER: SALEMP OKEGON:	(10) LOCATION OF WELL:	2998)
	111111111111111111111111111111111111111	
Name RON KILGOTE Address PENDLETON ORE		
Address PENDLETON ORE	NW 45W4 Section 26 T. 4N	
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivisi	on corner
New Well		
If abandonment, describe material and procedure in Item 12.	(44) ***********************************	
	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Sophi at White Wood Was Into Ioung	
Rotary Driven Domestic Industrial Municipal Cable Jetted	Static level ft. below land s	surface. Date 2-27-78
Dug	Artesian pressure lbs. per squar	e inch. Date
CASING INSTALLED: Threaded Welded	/40\ ************************************	1-6
16 " Diam. from +2 ft. to -4.8 ft. Gage 4250	(12) WELL LOG: Diameter of well below casing 15/2 Depth drilled 750 ft. Depth of completed well 750 ft.	
"Diam from ft. to ft. Gage		
"Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size	
	and show thickness and nature of each stratu with at least one entry for each change of forma	tion. Report each change in
PERFORATIONS: Perforated?	position of Static Water Level and indicate prin	cipal water-bearing strata.
Type of perforator used	MATERIAL	From To SWL
Size of perforations in. by in.	Soil	0 33
perforations from ft. to ft.	Baselt Broken	33 41
perforations from ft. to ft.	A BROWD	41 600
perforations from ft. to ft.	n GRey	100 150
(7) SCREENS: Well screen installed? Yes	Black Black	150 280
Manufacturer's Name	Rep + BRN w/ role	
Type Model No.	11 Black	305 421
Diam, Slot size Set from ft. to ft.	n GRey	490 515
Diam Slot size Set from ft. to ft.	" GREV	515 560
	h Black	560 600
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	" Black of Telc	600 615
Was a pump test made? The Yes No If yes, by whom? Walley	4 Black	615 710
Yield: 4000 gal./min. with 90 ft. drawdown after 8 hrs.	11 BROWN W/RED/TELC	710 736 182
" " "	" GREY	736 750
" " " " " " " " " " " " " " " " " " "		
Bailer test gal./min. with ft. drawdown after hrs.		
Artesian flow g.p.m.		
erature of water 70° Depth artesian flow encountered ft.	Work started 2-9 19 78 Complete	ed 2-27 1978
(9) CONSTRUCTION:	Date well drilling machine moved off of well	2-27 1978
Well seal—Material used PORT Law D COMENT	Drilling Machine Operator's Certification:	
Well sealed from land surface to 48 ft.	This well was constructed under my Materials used and information reported	direct supervision.
Diameter of well bore to bottom of seal 22 in.	best knowledge and belief.	
Diameter of well bore below seal	[Signed] (Drilling Machine Operator)	Date 2-27 , 19 78
Number of sacks of cement used in well seal	Drilling Machine Operator's License No. 933	
How was cement grout placed? GREUITY	Dining Machine Operator's License No.	
് വാട്ടി	Water Well Contractor's Certification:	,
The second secon	This well was drilled under my jurisd	iction and this report is
Was a drive shoe used? Yes No Plugs Size: location ft.	true to the best of my knowledge and belief.	
Did any strata contain unusable water? Yes Ao	Name L2 RR7 BURD Well DRILL/16 (Person, firm or corporation) (Type or print)	
Type of water? depth of strata	Address KS43 3W DOUGL	
	Andress Harris Control of the Contro	T
Method of sealing strata off	[Signed] Juy July	
Was well gravel packed? Yes No Size of gravel:	(Water Well Contr	The second of th
Gravel placed from ft. to ft.	Contractor's License No5.4.4. Date	<u> </u>
TIET ADDITIONAL OF	TERMO IN MINOROGADES	OTHER COM

158 12th Street NE Salem, OR 97310

(Office use only)

Well Identification Number:

RECEIVED

.IIIN 3 0 1999