STATE OF OREGON

WATER WELL REPORT APR 1 7 1986 (as required by ORS 537/95) (IT SOURCE

RECEIVEDUMAT PLEASE TYPE or PRINT IN INK

RECEIVED

MAY 1 2 1986

OURCES DEPT	TIMIEN RESOURCES DEPT (for official use only)
(1) OWNER:	(10) LOCATION OF WELL by legal description;
	1/10011/10
	101
Address Rt. 2, BOX 94 City Fendleton State OR 97801	Township (Township is North or South), Range (Range is East or West)
	Tax Lot Lot Block Subdivision
(2) TYPE OF WORK (check):	MAILING ADDRESS OF WELL for nearest address
New Well Deepening Reconditioning Abandon D	MT. S. BOX 94
If abandonment, describe material and procedure in Item 12.	- Pendleton, OR 9780/
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL of COMPLETED WELL:
Rotary Air Driven Domestic Industrial Municipal	Depth at which water was first found ft.
Rotary Mud Dug Irrigation Withdrawal Reinjection	Static level ft. below land surface. Date
Other:	Artesian pressure lbs. per square inch. Date
able Bored Piezometric Grounding Test	(12) WELL LOG: Diameter of well below casing
CASING INSTALLED: Steel Plastic	(12) WELL LOG: Diameter of well below casing
Threaded \square Welded \square	Formation: Describe color, texture, grain size and structure of materials; and show thickness
// Diam. from ft. to _/8.3 ft. Gauge 250	and nature of each stratum and aquifer penetrated, with at least one entry for each change of
ft. to ft. Gauge	formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
LINER INSTALLED: Steel Plastic	
LINER INSTALLED: Steel	MATERIAL From To SWL
"Diam. fromft. to	Meconditioning Procedure
(6) PERFORATIONS: Perforated? Yes No	Keamed hole from
(6) PERFORATIONS: Perforated? Size of perforations in. by in.	12" to 15" from
A STATE OF THE STA	77 + + + 0 /95 + + .
perforations from	Set 183 ft. 10" casing,
perforations from	cemented in place
perforations from ft. to ft.	with 150 sacks cement
(7) SCREENS: Well screen installed? Yes Wood No.	Drilled out plue
Manufacturer's Name	Cleaned out usell
TypeModel No	
Diam. Slot Size Set from ft. to ft.	
Diam. Slot Size Set from ft. to ft.	,
Drawdown is amount mater level is lowered	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? Yes No If yes, by whom?	
d: gal./min. with ft. drawdown after hrs.	
N N N N N N N N N N N N N N N N N N N	
Air test 2.000 + gal./min. with drill stem at 200 ft. hrs.	
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	
Imperature of water Depth artesian flow encountered	
	Date work started 3-210-1/2 /completed 3-21-1/2
9) CONSTRUCTION: Special standards: Yes \(\text{No } \textstyle \)	Date well drilling machine moved off of well 3 - 19 19
Well seal—Material used	(unbonded) Water Well Constructor Certification (if applicable):
Well sealed from land surface to ft.	This well was constructed under my direct supervision. Materials used and
Diameter of well bore to bottom of seal in.	information reported above are true to my best knowledge and belief.
Diameter of well bore below sealin.	microscop open and to the to my sold microscope and sold in
Amount of sealing material pounds pounds	[Signed] Date, 19
How was cement grout placed? ** TESSUTE 9 Touted	(bonded) Water Well Constructor Certifications
J	Bond SB 36090 Issued by Oregon Automobile Trisc
	(Surety Company Name)
Was pump installed? Depth ft.	On behalf of Tatrick C. Uk./ace. Uk./ace. Drilli
Was a drive shoe used? Yes No Plugs Size: location ft.	(cype or print name or water wen Constructor)
Did any strata contain unusable water? Yes No	This well was drilled under my jurisdiction and this report is true to the
Type of Water? depth of strata	best of my knowledge and belief:
Method of sealing strata off	(Signed) Patrick C Tallace
Was well gravel packed? Yes No Size of gravel:	(Water Well Constructor)
Gravel placed from ft. to ft.	(Dated) ————————————————————————————————————