WATER WELL REPORT STATE OF OREGON

REC

FEB ? - 1985/

UMAT WATER TREE WINGES TO SALEM SOLEM

State Well No.

State Permit No.

SALEM, OREGON

(1) OWNER:	(10) LOCATION OF WELL:	
Name Jin Brown	County UMETILLA Driller's well	number
Address ROUTE & PENDLETON OR	NE /2 NE 4 Section 15 T. 1N	R. 32 E W.M.
City State	Tax Lot # Lot_ Blk	Subdivision
(2) TYPE OF WORK (check):	Address at well location:	1.
New Well Deepening Reconditioning Abandon	(11) WATER LEVEL: Completed w	ell.
If abandonment, describe material and procedure in Item 12.	Depth at which water was first found	1 5%
(3) TYPE OF WELL: (4) PROPOSED USE (check):	110	
Rotary Air Driven Domestic Industrial Municipal	• -	and surface. Date er square inch. Date
Rotary Mud	·	
☐ Bored ☐ Thermal: Withdrawal ☐ Reinjection ☐	(12) WELL LOG: Diameter of well below	casing 6 3/16
(5) CASING INSTALLED: Steel & Plastic	Depth drilled 350 ft. Depth of	completed well 350 ft.
Threaded U Wolded A	Formation: Describe color, texture, grain size and stru	
8 "Diam from +2 ft to 150 ft. Gauge 250	thickness and nature of each stratum and aquifer pene for each change of formation. Report each change in	
"Diam from	and indicate principal water-bearing strata.	position of Saute Mater 25.01
LINER INSTALLED:	MATERIAL	From To SWL
	<u> </u>	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
	Soil	-
(6) PERFORATIONS: Perforated? Yes Z-No	GRAVEL	3 125
Type of perforator used	BROWN BASALT	125 190
Size of perforations in. by in.	GRAY	190 200
perforations from	BROWN	200 240
perforations from	ReD	240 250
perforations from	BROKEN BROWN	250 255
	GRAY	255 295
(7) SCREENS: Well screen installed? Yes You	BROWN	295 305
Manufacturer's Name	BROWN RED	305 3/0
Type Model No	- B ROWN	3/0 350
Diam. Slot Size Set from ft. to ft.		
Diam. Set from ft. to ft. to ft.	4 5	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
below south level	-	
Was a pump test made? ☐ Yes 🕩 No If yes, by whom?		
d: gal./min. with ft. drawdown after hrs.		
" " "	· 	
Air test 150 gal./min. with drill stem at 325 ft. 1 hrs.		
Bailer test 75 gal/min. with ft. dawdoon after / hrs.	- 1 - 1 - 1	
Artesian flow g.p.m.		
perature of water 5% Depth artesian flow encountered ft.	Work started /-/6 1985 Complet	ed 1-17 1985
(9) CONSTRUCTION: Special standards: Yes D No D	Date well drilling machine moved off of well	1-18 1985
Well seal—Material used PORTLEND COMONT	(unbonded) Water Well Constructor Certif	
Well sealed from land surface to 150 ft.		
Diameter of well bore to bottom of seal	This well was constructed under my direct and information reported above are true to my h	supervision. Materials used best knowledge and belief.
Diameter of well bore below seal		Date 1-181985
Number of sacks of cement used in well seal		
700410	bonded water well Constructor Certification:	
How was cement grout placed?	BondIssued by:	
THE CONTROL OF THE CO	This well was drilled under my jurisdiction	
Was pump installed?	the best of my knowledge and belief.	
Was a drive shoe used? ☐ Yes ♣No Plugs	Address 5543 S.W. Douglas;	Pond (Type or print)
Type of Water? depth of strata	[Signed] Water Well Constru	· · · · · · · · · · · · · · · · · · ·
Method of sealing strata off	Water Well Construc	etor
Was well gravel packed? Yes No Size of gravel: Gravel placed from ft to ft	Date	1-18 , 1985
crover naced from 11. 10 tt	I .	