E TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

report GEIVED

(Please type or print)

MAY 11 1976 State Well No. 11/32E3/

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

within 30 days from the date of well completion. (Please type	ove this INTER RESOURCES tabs Permit No.		
Page			
(1) OWNER:	(10) LOCATION OF WELL:		
Name R. M. Vandupol	County Umalilla Driller's well number		
Address Palor Rock Oragon	SW 14 NE 14 Section 21 T. 171, R. 32 E. W.M.		
(1) WYW ON WORK (1 1)	Bearing and distance from section or subdivision corner		
(2) TYPE OF WORK (check):			
New Well & Deepening Reconditioning Abandon			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 13 ft.		
Rotary L Driven Domestic Industrial Municipal Cable Jetted	Static level //O ft. below land surface. Date 4-6-76		
Dug Bored I Irrigation M Test Well Other I	Artesian pressure Ibs. per square inch. Date		
CASING INSTALLED: Threaded Welded 12	(12) WELL LOG: Diameter of well below casing 8 255 to 39		
10 " Diam. from 0 ft. to 21 ft. Gage , 250	Depth drilled 390 ft. Depth of completed well 390 ft.		
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,		
DEDICOD A MICONIC.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.		
PERFORATIONS: Perforated? Yes No.			
Type of perforator used	MATERIAL From To SWL		
Size of perforations in. by in.	Topsail 0 2		
perforations from ft. to ft.	Clayatine 2 13		
perforations from ft. to ft.	Roil, broken 13 15 Boscer, Kard black 15 33		
perforations from ft. to ft.	Boscer Kard black 15 33 Rock, light brown 33 41		
(7) SCREENS: Well screen installed? Yes LNo	Rab mid black 4154		
Manufacturer's Name	Basalt Kurd black 54 71		
Type Model No.	Rock black + brown + 71 80		
Diam. Slot size Set from ft. to ft.	- blue chargetime		
Diam, Slot size Set from ft, to ft.	Rack, light brown 80 83		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Rock, red 4 yellow claydon 83 105 W.B.		
	Rock hard brown 1 105 108		
Was a pump test made? 🗌 Yes 🦞 No If yes, by whom?	Basalt hard, black 108 118 Basalt hard grass 118 162		
Yield: gal./min. with ft. drawdown after hrs.	Rock, grey redalling everyton 162 165		
" " "	Rock, darb brownshin classion 165 170		
" " "	Rock, durk brown hard 170 177		
Baffer-test 500 gal./min. with 250 ft. drawdown after / hrs.	Basalt, Kard, black 177 203		
Artesian flow g.p.m.	Basalt, Kurd, gray 203 218		
perature of water Depth artesian flow encounteredft.	Work started 3-29 1976 Completed 4-6 1976		
(9) CONSTRUCTION:	Date well drilling machine moved off of well 4-6 1976		
Well seal-Material used Cerrent	Drilling Machine Operator's Certification:		
Well sealed from land surface to 21 ft.	This well was constructed under my direct supervision.		
Diameter of well bore to bottom of sealin.	Materials used and information reported above are true to my best knowledge and belief.		
Diameter of well bore below sealin.	[Signed] A state of the Date 4-6 1976		
Number of sacks of cement used in well sealsacks	(Drilling Machine Operator)		
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No		
Brand name of bentonite	Water Well Contractor's Certification:		
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is		
of waterlbs./100 gals.	true to the best of my knowledge and belief.		
Was a drive shoe used? Yes No Plugs Size: location ft.	Name TROY GRIFFIN		
Did any strata contain unusable water? ☐ Yes 🔂 No	(Person, firm or corporation) (Type or print) Address 900 HERMISTON AVE, HERMISTON ORE		
Type of water? depth of strata	Address Lumitica-military in Marketing Control of the Control of t		
Method of sealing strata off	[Signed] (Water Well Contractor)		
Was well gravel packed? Yes S No Size of gravel:			
Gravel placed from ft. to ft.	Contractor's License No. 6.5 Date 4-4 , 1975		

IOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

UMAT WATER WELL REPORTE CEIVED

STATE OF OREGON

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

(Please type or print)

MAY 11 1975 Well No.

within 30 days from the date	bove this line), TER RESOURCES BERT NO) .
of well completion. (Do not write a	CON SALEM OFFICEN	
(1) OWNER: 6-7327	(10) LOCATION OF WELL:	
Name R. N. Van dubel	County Umatilla Driller's well nu	mber
Address Pilor Ruck, Origin 97868	& W 14 M.E. 14 Section 21 T. IM	
P.O. Boy 13.5	Bearing and distance from section or subdivision	n corner
(2) TYPE OF WORK (check):		
New Well 5. Deepening Reconditioning Abandon		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed we	:ll.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	ft
Rotary Driven Domestic Industrial Municipal	Static level ft. below land su	ırface. Date
Cable	Artesian pressure lbs. per square	inch. Date
	Too per square	
(a) CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing	
"Diam. from ft. to ft. Gage ft. Gage ft. to ft. Gage	Depth drilled ft. Depth of comple	ted well ft.
"Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated.	
(6) PERFORATIONS: Perforated? Yes No.	with at least one entry for each change of formati position of Static Water Level and indicate princ	
	MATERIAL	
Type of perforator used		214 224
Size of perforations in. by in.	Kick brown T geller cloyeting	218 239 WB
perforations from	Koip, disposion	239 243 W.B.
perforations from ft. to ft.	Philip Park Hard	245 245
perforations fromft. toft.	Bound and Chan	245 255
(7) SCREENS: Well screen installed? Yes No	Park And	328 356 W.B
Manufacturer's Name	Boards Load Osci	357. 377
Type	Rock, brown, hohen amt	317 390 W.B.
Diam. Slot size Set from ft. to ft.		377 370
Diam Slot size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is		
TOWELEST DELOW SERVIC TEVEL		
Was a pump test made? Yes No If yes, by whom?		
Yield: gal./min. with ft. drawdown after hrs.		
н н		
"		
Bailer test gal./min. with ft. drawdown after hrs.		
Artesian flow g.p.m.		
perature of water Depth artesian flow encountered ft.	Work started 19 Completed	19
(9) CONSTRUCTION:	Date well drilling machine moved off of well	19
Well scal—Material used	Drilling Machine Operator's Certification:	
Well sealed from land surface to ft.	This well was constructed under my Materials used and information reported	
Diameter of well bore to bottom of sealin.	best knowledge and belief.	move are are to my
Diameter of well bore below seal in.	[Signed] [Drilling Machine Operator)	Date, 19
Number of sacks of cement used in well seal sacks		
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No	
Brand name of bentonite	Water Well Contractor's Certification:	
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdic	tion and this report is
of waterlbs./100 gals.	true to the best of my knowledge and belie	
Was a drive shoe used? Yes No Plugs Size: location ft.	Name TRIY GRIFFIH (Person, firm or corporation)	
Did any strata contain unusable water? Yes No	(Person, firm or corporation) Address 900.HERM 1.370H AVE, HE	(Type or print) FPA 1577N ORE
Type of water? depth of strata	Address 7.0.6 MEK MI 121011 TVC, TZ	A // 13/011 022
Method of sealing strata off	[Signed]	
Was well gravel packed? Yes No Size of gravel:	(Water Well Contra	ctor)
Gravel planed from # to #	Contractor's License No. Date	19