NOTICE TO WATER WELL CONTRACTOR The original and first copy	RECEIVED ba
of this report are to be filed with the UMA TATER WELL REPORT STATE OF OREGON FEB21 1974 State Well No. 4-N/35E-35	
STATE ENGINEER, SALEM, OREGON 97310 2102/ (Please type or print) STATE ENGINEER	
within 30 days from the date of well completion. (Do not write ab	or print) STATE ENGINEERState Permit No.
	(10) LOCATION OF WELL:
(1) OWNER: $A \mu R (A) = T \mu C$	County UMATILLA Driller's well number 4240
Address DD Box 109 WESTON ORE	. NE 1/4 Multi Section 35 T. 4N R. 35 E. W.M.
Address P.O. Day TO PORCHUT She	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	Bearing and distance from section of subdivision corner
New Well 🔲 Deepening 🗌 Reconditioning 🔯 Abandon 🗌	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found
Rotary D. Driven D. Domestic D. Industrial Municipal D	Static level 384 ft. below land surface. Date 1/17/74
Cable X Jetted Distribution Distribution Distribution Dug Bored Inrigation Test Well Other Initiation	Artesian pressure Ibs. per square inch. Date
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing
20" Diam. from +1 ft. to 37 ft. Gage 375	Depth drilled ft. Depth of completed well $1/25$ ft.
	Formation: Describe color, texture, grain size and structure of materials;
	and show thickness and nature of each stratum and aquifer penetrated,
PERFORATIONS: Perforated? Yes XNo.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	NO ADDITIONAL DEILLING
ft. to ft.	WAS DONE BUT THE WELL
perforations from ft. to ft.	WAS REAMED AS TOLLOUDS.
ft. to ft.	THE WELL WAS REAMED FROM
(7) SCREENS: Well screen installed? Yes XNo	JUFT DEPTH TO 31FT DEPTH
Manufacturer's Name	TO 23 IN DIA, AND 20 IN.
Type Model No.	CASING INSTALLED AND
Diam Slot size Set from ft. to ft.	GROUTED IN PLACE
Diam	THE 12 IN HOLE INAS
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	REAMED FROM 37FT DEDTH
Was a pump test made? Yes No If yes, by whom?	TO 608 FT. TO 1910 DIA.
Yield: gal./min. with ft. drawdown after hrs.	
" " " "	THE 8IN HOLE WAS KEAMED
<i>II II </i>	FROM GOSTF DEMA TO THE
Bailer test gal./min. with ft. drawdown after hrs.	$-\frac{10}{12} \frac{12}{10} \frac{11}{10} \frac{11}{10}$
Artesian flow g.p.m.	
Depth artesian flow encountered ft.	Work started OCT/6 1973 Completed FEB/1974
(9) CONSTRUCTION:	Date well drilling machine moved off of well 755/1974
Well seal-Material used SAND AND CEMENT GROUT	-Drilling Machine Operator's Certification: This well was constructed under my direct supervision.
Well sealed from land surface toft.	Materials used and information reported above are true to my
Diameter of well bore to bottom of seal	best knowledge and belief.)
Diameter of well bore below seal 16 . AND the 100 sacks of cement used in well seal	[Signed]
Number of sacks of bentonite used in well seal	Drilling Machine Operator's Bicense No.
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is
of water	true to the best of my knowledge and belief.
Was a drive shoe used? Yes No Plugs	Name KJ STRASSER DRILLING LO
Did any strata contain unusable water? 🗌 Yes 🗋 No	Address SILOSE SUNSETLANE TOPTLAND
Type of water? depth of strata	Autress the transferred to the t
Method of sealing strata off Was well gravel packed? Yes No Size of gravel:	[Signed] (Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 10 Date FEB 18, 1974
	HEETS IF NECESSARY) SP*45656-119

-