	heivee	TIAA A	**		
NOTICE TO WATER WELL CONTRACTOR	and the same of th	33			
The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM 10, OREGON	· · · · · · · · · · · · · · · · · · ·	ELL REPORT  F OREGON	State Well No	//31-	-7
within 30 days from the date of well completion.	(Please ty	pe or print)	State Permit No	***********	
(1) OWNER: Name Wr. D. Henry Roberts		(11) WELL TESTS: Drawdown is amount water level is lowered below static level			
Address BOX 340		Was a pump test made? ☐ Yes 本 No If yes, by whom?  Yield: gal./min. with ft. drawdown after hrs.			
Pilot Rock, Oregon		" "	"it. drawd	own arter	hrs.
(2) LOCATION OF WELL:		"			
County Umatilla Driller's well number		Bailer test 10 gal./min. with 36 ft. drawdown after 1 hrs.  Artesian flow			
14 14 Section 7 T. 1 R. 31 E W.M.		Artesian flow g.p.m. Date  Temperature of water Was a chemical analysis made?  Ves  No			
Bearing and distance from section or subdivisi	on corner	(12) WELL LOG:		~ .	LES LINO
	•	Depth drilled 136	Diameter of well below of tt. Depth of completed v	vell 136	ft.
	3	Formation: Describe by cold show thickness of aquifiers stratum penetrated, with at			
(9) MYDE OF MODIC (-11-)		MAT	ERIAL	FROM	то
(3) TYPE OF WORK (check): New Well X Deepening  Recond	Soil		0	14	
If abandonment, describe material and proced	Rock, grey Rock, blue		14	27	
(4) PROPOSED LISE (about).	(E) BANDE OF MARK	Rock, grey		27 54	<u>54</u> 88
(4) PROPOSED USE (check):  Domestic Industrial Municipal	(5) TYPE OF WELL:  Rotary □ Driven □	Rock, blue	- 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	88	98
Irrigation   Test Well   Other	Cable K Jetted □ Dug □ Bored □	Rock, red, wat	er	98	122
(6) CASING INSTALLED: Threaded ▼ Welded □  8 " Diam. from 0 ft. to 18 ft. Gage 277  " Diam. from ft. to ft. Gage " Diam. ft. Gage " Diam. from ft. to ft. Gage " Diam. ft		Rock, blue		122	136
(7) PERFORATIONS: Personal Type of perforator used	forated? 🗌 Yes 🍒 No		en e		
Size of perforations in. by in.			T.		
perforations fromft. toft.			X 18	+	
perforations from					
perforations from			1.000 300 <del>00</del>		
perforations fromft. toft.					
		7 (20)			
(8) SCREENS: Well screen installed?  Well screen installed?  Yes X No Manufacturer's Name			And the second s		
Туре Мо		- 100			
Diam Slot size Set from		Work started July 2:	l 19 64 Completed A	ug 14	
Diam. Slot size Set from	ft. to ft.	Date well drilling machine n		ug 18	19 64
(9) CONSTRUCTION:		(13) PUMP:	_	<u> </u>	19 64
Well seal-Material used in seal Padded	clay				
Depth of seal18ft. Was a packer used?		Manufacturer's Name Type:			
Diameter of well bore to bottom of seal11 in.				D.P	
Were any loose strata cemented off? Yes	No Depth	Water Well Contractor's	Certification:		
Was a drive shoe used?   Yes □ No Was well gravel packed? □ Yes   No Si	ze of gravel:	This well was drilled true to the best of my kn	under my jurisdiction owledge and belief.	and this r	report is
Gravel placed from ft. to ft.		NAMEJohn Hershey Well Drilling			
Did any strata contain unusable water? 🔲 Yes 🌠 No		(Person, firm or corporation) (Type or print)			
Type of water? Depth of st	Address R.R.1, Box 552, Hermiston, Oregon				
Method of sealing strata off	Drilling Machine Operator's License No143				
(10) WATER LEVELS: Static level 90 ft. below land a	[Signed]	2 Hersle	4		
Static level 90 ft. below land surface Date8/14/64  Artesian pressure lbs. per square inch Date		Contractor Ticanso No	(Water Well Contractor	8	6.4