WATER WELL REPORT STATE OF OREGON



RECEIVED to Well No. 5M 28E-

APR 4 1983 State Permit No.

	WATER RECOGNOES DEPT. Kee	molloning
(1) OWNER:	(10) LOCATION OF WELL:	\supset
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	County Umatilla Driller's well r	number
Address Rt. 1. Box /418		R. 28 W.M.
City Herniston State Or. 97838	Tax Lot # Lot Blk	Subdivision
	Address at well location: Rt. 1. Box 1498	}
(2) TYPE OF WORK (check):	Hermiston Or	-, 97838
New Well □ Deepening □ Reconditioning □ Abandon □	(11) WATER LEVEL: Completed we	all.
If abandonment, describe material and procedure in Item 12.	Depth at which water was first found	/67 ft.
(3) TYPE OF WELL: (4) PROPOSED USE (check):		nd surface. Date, 3-5-8
Rotary Air Driven Domestic Line Industrial Municipal .		square inch. Date
tary Mud Dug	(12) WELL LOG: Diameter of well below of	7 //
	1 N	ompleted well 250 ft.
(5) CASING INSTALLED: Steel Plastic Threaded Welded	Formation: Describe color, texture, grain size and structure	
	thickness and nature of each stratum and aquifer penet	rated, with at least one entry
"Diam from ft. to ft. Gauge	for each change of formation. Report each change in p and indicate principal water-bearing strata.	ostion of Static Water Level
LINER INSTALLED:	MATERIAL	From To / SWL
	1 - O - 1 - 2 - 1	Trom 10 SWI
	andy Soil	111 25
(6) PERFORATIONS: Perforated? ☐ Yes No	Gravell & boulders	17 00
Type of perforator used	Grey Dasalt	167 180 Wate
Size of perforations in. by in.	Soft porous redt grey basalt	
perforations from	Grey basalt w/ soapstone	180 204
perforations from ft. to ft.	Grey Dasalt	207 250
perforations from ft. to ft.		
(7) SCREENS: Well screen installed? Yes DNo		
Manufacturer's Name		
Type Model No.	- / Ac #	
Diam. Slot Size Set from ft. to ft.		
Diam. Slot Size Set from ft. to ft.		
Drawdown is amount water level is lowered		
(8) WELL TESTS: below static level		
as a pump test made? 🗆 Yes 🕡 No If yes, by whom?		
Yield: gal./min, with ft. drawdown after hrs.		
H " "	the second second	
Air test /50 gal./min. with drill stem at 250 ft. hrs.		
Bailer test gal./min. with ft. drawdown after hrs.	4 4 4	
Artesian flow g.p.m.		
Temperature of water Depth artesian flow encountered ft.	Work started 3-4 1983 Complete	d 3-5 196
(9) CONSTRUCTION: Special standards: Yes □ No 🖟	Date well drilling machine moved off of well	<u>3-5 198.</u>
Well seal—Material used	(unbonded) Water Well Constructor Certifi	cation (if applicable):
Well sealed from land surface toft.	This well was constructed under my direct s	
Diameter of well bore to bottom of seal	and information reported above are true to my b	
Diameter of well bore below sealin.	[Signed]	. Date, 19
Number of sacks of cement used in well seal sacks	Bonded Water Well Constructor Certificati	on:/
How was cement grout placed? Them Ped With	Bond S B 36090 Issued by: () Fegor	. Hutomobile L
trimmy pipes	(number) Sur This well was drilled under my jurisdiction	ety Company Name
/ //	the best of my knowledge and belief.	. a.ra arro roporo io arae a
Was pump installed?	Name Wallace Drilling	/Tume
Was a drive shoe used? Wes No Plugs	Address 1307 SW23-1 Pend 6	ton. () r. 97801
Did any strata contain unusable water? Yes Voo	THUIS PARTY OF THE PROPERTY OF THE PARTY OF	10
Type of Water? depth of strata	[Signed] . Water Well Construct	Class -
Method of sealing strata off Was well gravel packed? □ Yes □ No Size of gravel:	Date	3-19 1983
Gravel placed from		