NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion. WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

UMA T 3546 State Well No. 51/286-34db

(1) OWNER:	(10) LOCATION OF WELL:	
Name Ed Mac Shegor	County Umatila Driller's well number	
Address 4028 S. E. Aldercust Rd	71. W 14 & E 14 Section 34 T. 571. R. 28 E. W.M.	
Milwankin, Oregon 91222	Bearing and distance from section or subdivision corner	
(2) TYPE OF WORK (check):		
New Well A Deepening Reconditioning Abandon		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 93 ft.	
Rotary Driven Domestic Mindustrial Municipal Domestic	Static level 104 ft. below land surface. Date 5-28-80	
Bored ☐ Irrigation ☐ Test Well ☐ Other ☐	Artesian pressurelbs. per square inch. Date	
(5) CASING INSTALLED: Threaded Welded W	(12) WELL LOG: Diameter of well below casing 6"	
6 "Diam. from 4/ ft. to 149 ft. Gage .250	Depth drilled 300 ft. Depth of completed well 300 ft.	
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials;	
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrated.	
(6) PERFORATIONS: Perforated? Yes Z No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.	
Type of perforator used		From To SWL
Size of perforations in. by in.	Topsoil	0 3
perforations fromft. toft.	Sand gray	3 7/
perforations fromft. toft.	Sand + graves	71 81
perforations from ft. to ft.	Claratine + gravel	81 93
(7) SCREENS: Well screen installed? Ver M No.	Classing sand	73 107 W.B.
(1) SCREENS: Well screen installed? Yes M No Manufacturer's Name	Sand, blue 4 gravel	07 144 4.8.
TypeModel No.	Kock, black of blue Claystone 1	44 /71
Diam. Slot size Set from ft. to ft.	Basely and Olam	62 785
Diam. Slot size Set from ft. to ft.	Rock black 2	85 300 W.B.
(8) WELL TESTS: Drawdown is amount water level is		
lowered below static level	RECEIVED	
a pump test made? Yes No If yes, by whom?	UNIT 03000	
Yield: gal./min. with ft. drawdown after hrs.	JUN 1 9 1980	
	WATER RESOURCES DEPT	
A-IR TEST 100 " 96 " 1 "	SALEM, OREGON	
test 60 gal./min. with 49 ft. drawdown after / hrs.		
A sian flow g.p.m.		
Temperature of water Depth artesian flow encountered ft.	Work started 5-25 1980 Completed	5-28 1980
(9) CONSTRUCTION:	Date well drilling machine moved off of well	5.28 1980
Well seal—Material used Cement	Drilling Machine Operator's Certification:	
Well sealed from land surface toftftftft	This well was constructed under my direct supervision. Materials used and information reported above are true to my	
Diameter of well bore to bottom of seal 10" to 30' in Lower red	best knowledge and belief.	
Diameter of well bore below sealin.	[Signed] Janua Total Date 5-28, 1980 (Drilling Machin Operator)	
Number of sacks of cement used in well seal	Drilling Machine Operator's License No. 665	
how was cement grout placed? Authors growth miss	Diffing Machine Operator's Dicense 140w.w.	
## ## ## ## ## ## ## ## ## ## ## ## ##	Water Well Contractor's Certification:	under haum innere antere
	This well was drilled under my jurisdiction and this report is	
Was a drive shoe used? 🥦 Yes 🗌 No Plugs Size: location ft.	true to the best of my knowledge and belief. Name TRUY GRIFFIM	
Did any strata contain unusable water? 🔲 Yes, 🕱 No	(Person, firm or corporation) (Type or print)	
Type of water? depth of strata	Address 900 HER MISTON AVE	FERMISTON OF
Method of sealing strata off	[Signed] Joseph	à:
Was well gravel packed? [Yes K No Size of gravel:	[Signed] (Water Well Contracto	
Gravel placed fromft. toft.	Contractor's License No Date	5-28 1980