NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the WATER WE	OREGON CEIVE The Well No.	EN/DRE-341
STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion. (Please typ (Do not write a	it i go to - State Down it i	No
(1) OWNER:	(10) LOCATION OF WELL!	
Name Dermiston day Care Center	County Umalilla Driller's well number	
Address Demustor Oregon 97838	SW 1/2 S. E 1/4 Section 34 T. 5 N. R. 28 E, W.M.	
	= Bearing and distance from section or subdivision corner	
(2) TYPE OF WORK (check):		
New Well A Deepening Reconditioning Abandon		
If abandonment, describe material and procedure in Item 12.	- (11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 130 ft.	
Rotary X Driven Cable Jetted Domestic X Industrial IMunicipal	Static level 89 ft, below land surface. Date 12-8-76	
Dug 🔲 Bored 🗌 Irrigation 🗌 Test Well 🗌 Other 🗌	Artesian pressure lbs. per squa	re inch. Date
CASING INSTALLED: Threaded D Welded		1.11
6 " Diam. from 6 ft. to 144 ft. Gage 250	(12) WELL LOG: Diameter of well below casing 6"	
" Diam. from ft. to ft. Gage	Depth drilled 304 ft. Depth of completed well 304 ft.	
	Formation: Describe color, texture, grain size and show thickness and nature of each stratu	m and aquifer penetrated
PERFORATIONS: Perforeted?	with at least one entry for each change of forms position of Static Water Level and indicate prin	tion. Report each change in
Type of perforator used		T
	MATERIAL	From To SWL
	Topsoil	0 2
perforations from ft. to	- Gand	$\frac{2}{30}$ $\frac{130}{136}$ $\frac{136}{10.5}$
perforations from	Classtone, blue	130 136 W.B. 136 178
	Basall	178 281
(7) SCREENS: Well screen installed? Yes XNo	Rock, black	281 304 W.B.
Manufacturer's Name		
Type Model No ft ft. to ft.		
Diam		· · · · · · · · · · · · · · · · · · ·
		<u>├</u>
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	<u>926108036</u>	
Was a pump test made? 🔲 Yes 🕅 No If yes, by whom?		
Vield: gal./min. with ft. drawdown after hrs.		
Citra management		
Ballor test 75 gal./min. with /// ft. drawdown after / hrs.		
esian flow g.p.m.		
perature of water Depth artesian flow encountered	Work started 11 - 26 1976 Complete	ed 12-8 1976
(9) CONSTRUCTION:	Date well drilling machine moved off of well	12-8 1976
Well seal-Material used Ciment	Drilling Machine Operator's Certification:	
I sealed from land surface to 35	This well was constructed under my	direct supervision.
Diameter of well bore to bottom of seal in.	Materials used and information reported best knowledge and belief	
Diameter of well bore below seal	[Signed] . [very Swaffin -	Date 12-10, 1976
Number of sacks of cement used in well seal	(Drilling Machine Operator) Drilling Machine Operator's License No.	
Number of sacks of bentonite used in well seal sacks Brand name of bentonite		
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:	æ., . ⁻
of water Ibs./100 gals.	This well was drilled under my jurisdi	ction and this report is
Was a drive shoe used? 🗗 Yes 📋 No Plugs Size: location	true to the best of my knowledge and bell Name $TRUV$ $GR/FF/M$	lei.
Did any strata contain unusable water? 🔲 Yes 🕱 No	(Person, firm or corporation)	(Type or print)
Type of water? depth of strata	Address 900 HERMISTOHAVE 1	FERMISTON OP
Method of sealing strata off	[Signed] - Twee Struct	fin.
Was well gravel packed? 🗋 Yes 🙀 No Size of gravel:	(Water Well Contr	Actor)
		1 -
Fravel placed from ft. to ft.	Contractor's License No Date	12-10 1976