NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report

are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT CEIVED

STATE OF OREGON MAY 1 91977 State Well No. 5N/28E-35cc.
(Please type or print)

(1) OWNER:	(10) LOCATION OF WELL:
Name Lyle Tilden	County Umatilla Driller's well number
Address Rta By 2408	&V 4 &W 4 Section 35 T. 57 R. 28E. W.M.
Herniston Oregon 97838	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check)∜	
New Well 💆 Deepening 🗌 Reconditioning 🗎 Abandon 🗖	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	
Determine and Division II	Depth at which water was first found 105 ft.
Cable Jetted	Static level 88 ft. below land surface. Date 5-2-77
Dug ☐ Bored ☐ Irrigation 😿 Test Well ☐ Other ☐	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded ☐ Welded 🛣	(12) WELL LOG: Diameter of well below casing
8 " Diam. from 6 ft. to 120 ft. Gage 250	
	Depth drilled 120 ft. Depth of completed well 120 ft.
ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,
	with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	Topsoil 0 3
perforations from ft. to ft.	Sand 3 105
perforations from ft. to ft.	Skane 105 120 W.B.
perforations from ft. to ft.	
(7) COPERIG.	
(7) SCREENS: Well screen installed? ☐ Yes 🙀 No	
Manufacturer's Name	
Type Model No	
Diam. Slot size Set from ft. to ft. Diam. Slot size Set from ft. to ft.	
Diani, Stot size Set from 1t. to 1t.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? ☐ Yes 🖹 No If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs.	
· · · · · · · · · · · · · · · · · · ·	
Cirks 1 -	
Bailor test /50 gal./min. with 3 2 ft. drawdown after / hrs.	
Artesian flow g.p.m.	
perature of water Depth artesian flow encountered ft.	Work started 4-29 19 77 Completed 5-3 19 77
(9) CONSTRUCTION;	Date well drilling machine moved off of well 5-3 19 77
Well seal-Material used ement & bentonite	Drilling Machine Operator's Certification:
Well sealed from land surface to 26 ft.	This well was constructed under my direct supervision.
Diameter of well bore to bottom of sealin.	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal	[Signed] John Van Swall Date 5-3, 1977
Number of sacks of cement used in well seal 4+ 1/2 bentontsacks	(Drilling Machine Operator)
How was cement grout placed?	Drilling Machine Operator's License No. 1027
	Window Windle Communications Contidionations
	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? Yes No Plugs Size: location ft.	Name TROY GRIFFIN
Did any strata contain unusable water? Yes No	(Derson, firm or corporation) (Type or print)
Type of water? depth of strata	Address 900 HERMISTON AVE, HERMISTON, ORE
Method of sealing strata off	[Signed] Troy Suffen.
Was well gravel packed? Yes No Size of gravel:	(Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 65 Date
	