

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

WATER WELL REPORT

STATE OF OREGON

State Well No. ....

(Please type or print)

State Permit No. ....

(Do not write above this line)

STATE ENGINEER, SALEM, OREGON within 30 days from the date of well completion.

UMAT 2/21/74

RECEIVED JAN 26 1976 WATER RESOURCES DEPT. SALEM, OREGON

(1) OWNER:

Name Haagen Landover Hills Address 83 1/2 Mill Plain Blvd. Vancouver Wash. 98664

(2) TYPE OF WORK (check):

New Well [x] Deepening [ ] Reconditioning [ ] Abandon [ ] If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [x] Cable [ ] Dug [ ] Driven [ ] Jetted [ ] Bored [ ]

(4) PROPOSED USE (check):

Domestic [x] Industrial [ ] Municipal [ ] Irrigation [ ] Test Well [ ] Other [ ]

CASING INSTALLED:

6" Diam. from 0 ft. to 133 ft. Gage 250

PERFORATIONS:

Perforated? [ ] Yes [x] No

Type of perforator used

Size of perforations in. by in. perforations from ft. to ft.

(7) SCREENS:

Well screen installed? [ ] Yes [x] No

Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? [ ] Yes [x] No Yield: gal./min. with ft. drawdown after hrs. art test 75 110 1 art test 150 180 1

(9) CONSTRUCTION:

Well seal—Material used Cement & bentonite Well sealed from land surface to 133 ft. Diameter of well bore to bottom of seal 9 in. Diameter of well bore below seal 6 in. Number of sacks of cement used in well seal 5 sacks Number of sacks of bentonite used in well seal 1 sacks Brand name of bentonite National Number of pounds of bentonite per 100 gallons of water lbs./100 gals. Was a drive shoe used? [x] Yes [ ] No Plugs Size: location ft. Did any strata contain unusable water? [ ] Yes [x] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [ ] Yes [x] No Size of gravel: Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Umatilla Driller's well number N.W 1/4 N.W 1/4 Section 35 T. 57 R. 28 E. W.M. Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 126 ft. Static level 90 ft. below land surface. Date 1/20/76 Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6" Depth drilled 275 ft. Depth of completed well 275 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with 4 columns: MATERIAL, From, To, SWL. Rows include Topsoil, Sand, Coarse, Gray, Shales & claystone, Claystone, Blue, Rock black & blue claystone, Basalt, black, Basalt, hard, gray, Rock, black & green claystone, Basalt, black.

Work started 1-19 1976 Completed 1-20 1976 Date well drilling machine moved off of well 1-20 1976

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] James T Leitch Date 1/21, 1976 (Drilling Machine Operator) Drilling Machine Operator's License No. 665

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name TROY GRIFFIN (Person, firm or corporation) (Type or print) Address 900 HERMISTON AVE, HERMISTON ORE. [Signed] Troy Griffin (Water Well Contractor) Contractor's License No. 65 Date 1-21, 1976