NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report , are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

# 1	
State Well No. 5N/28E	-36cb
State Permit No.	
ELL:	
Driller's well number BL T. 571. R. 288.	W.M.
tion or subdivision corner	
-	
Completed well.	ft
ft. below land surface. Date 3	19-80
lbs. per square inch. Date	
amatan of small below as its	

(1) OWNER:	(10) LOCATION OF WELL:	
Name Truing J. Hardin	County Umatilla Driller's well number	
Address Rtz Bby 2873A	N.W 14 &W 14 Section 36 T. 571. R. 288. W.M.	
Hermiton Oregon 97838	Bearing and distance from section or subdivision corner	
(2) TYPE OF WORK (check): U		
New Well 5 Deepening Reconditioning Abandon	•	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 144 ft.	
Rotary M. Driven Domestic M. Industrial Municipal	Static level 100 ft. below land surface. Date 3-19-8cl	
Cable		
	Artesian pressure lbs. per square inch. Date	
(5) CASING INSTALLED: Threaded Welded 10	(12) WELL LOG: Diameter of well below casing	
	Depth drilled 165 ft. Depth of completed well 165 ft.	
	Formation: Describe color, texture, grain size and structure of materials;	
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrated,	
(6) PERFORATIONS: Perforated? Yes FL No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.	
Type of perforator used	MATERIAL From To SWL	
Size of perforations in. by in.	Typsoil 0 2	
perforations from	Sand, Gray 2 63	
perforations from	Sand + Clarothere blue 144 156 WB	
perforations from ft. to ft.		
(7) SCREENS: Well screen installed? Yes No	Travels 156 165 W.B.	
Manufacturer's Name	. 5 4	
Type Model No		
Diam Slot size Set from ft. to ft.		
Diam Slot size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is	HEL-EIVEU	
lowered below static level	MAR 2 6 1980	
Wes a pump test made? Yes No If yes, by whom?		
d: gal./min. with ft. drawdown after hrs.	WATER RESOURCES DEPT	
" " "	SALEM, OREGON	
IR 100 " 55 " 1 "		
AIR saller test 40 gal./min. with 25 ft. drawdown after 1 hrs.		
esian flow g.p.m.		
Temperature of water Depth artesian flow encounteredft.	Work started 3-18 1980 Completed 3-19 1980	
(A) GONGERANCE	Date well drilling machine moved off of well 3-/4 1980	
(9) CONSTRUCTION:		
Well seal—Material used	Drilling Machine Operator's Certification:	
Well sealed from land surface toft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my	
Diameter of well bore to bottom of seal in.	best knowledge and belief.	
Diameter of well bore below seal	[Signed] Anuly Jule Date 3-19, 1980 (Drilling Machine Operator)	
Number of sacks of cement used in well seal 15 sacks How was cement grout placed? P.La. cd & tremie Pupe	Drilling Machine Operator's License No. 665	
from bottom to top of onises I duce hole		
	Water Well Contractor's Certification:	
77	This well was drilled under my jurisdiction and this report is	
true to the best of my knowledge and belief.		
Did any strata contain unusable water? Yes No	Name TROY GRIFFIN (Person, firm or corporation) (Type or print)	
Type of water? depth of strata	Address 900 HER MISTON AVE, HERMISTON, OR	
Method of sealing strata off	Time Wall-	
Was well gravel packed? ☐ Yes 🌿 No Size of gravel:	[Signed] (Water Well Contractor)	
Gravel placed from	Contractor's License No. 65 Date 3-19 1984	
	CONTRACTOR'S LICENSE NO. Date Jan., 1999	
(ISE ADDITIONAL CE	DESCRIPTION OF THE PROPERTY OF	