NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

water resources department for salem, Oregon 97310 within 30 days from the date of well completion.

WATER WELL REPORTE CEIVED

STATE OF OREGON

NOV 13 1979 State Well No. 5N 28E-30

(Please type or print)

WATER RESOURCES BEPFrmit No.

(Do not write above this line)

SALEM, OREGON

(1) OWNER:	(10) LOCATION OF WELL:	
Name M. V. Wolverton	County Umatilla Driller's well number	
Address R. 2 Box 2875 Hermiston, Ore. 97838	SW 1/4 1/4 Section 36 T. 5N R. 28E W.M.	
	Bearing and distance from section or subdivision	on corner
(2) TYPE OF WORK (check):		
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 155 ft.	
Rotary K Driven Domestic Industrial Municipal Domestic	Static level 90 ft. below land s	surface. Date 11-7-79
Dug	Artesian pressure lbs. per square inch. Date	
(5) CASING INSTALLED: Threaded Welded 104 ft. Gage 250	(12) WELL LOG: Diameter of well be Depth drilled 164 ft. Depth of comple	
"Diam. from	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.	
(6) PERFORATIONS: Perforated? □ Yes 笆 No. Type of perforator used	MATERIAL	From To SWL
Size of perforations in. by in.	surface sand	0 3
perforations from ft. to ft.	sand brown	3 135
perforations from ft. to ft.	sand blue	135 155
perforations from ft. to ft.	sand & gravel	155 158 90
(E) CODDENC	gravel	158 164 90
(7) SCREENS: Well screen installed? Well screen installed? Yes No Manufacturer's Name		
Type Model No	-	
Diam Slot size Set from ft. to ft.	-	
Diam Slot size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
a pump test made? Yes No If yes, by whom?	,	
	<u></u>	
Yield: gal./min. with ft. drawdown after hrs.		
air " " " "		
<u> </u>		
r test gal./min. with 50 ft. drawdown after 2 hrs. Artesian flow g.p.m.		
Temperature of water Depth artesian flow encountered ft.	Work started 11-6-79 19 Complete	ed 11-7-79 19
(9) CONSTRUCTION:	Date well drilling machine moved off of well	1-7-79 19
Well seal—Material used Cement	Drilling Machine Operator's Certification:	
Well sealed from land surface toft.	This well was constructed under my Materials used and information reported	
Diameter of well bore to bottom of sealin. Diameter of well bore below sealin.	best knowledge and belief.	Date 11-8-79 19
6	(Drilling Machine Operator)	
How was coment grout placed? Run trimmy pipe to 18 ft.	Drilling Machine Operator's License No.	484
Pumped 6 sacks cement through pipe to land surface	Water Well Contractor's Certification:	
	This well was drilled under my jurisdiction and this report is	
Was a drive shoe used? ☐ Yes ᡯ No Plugs Size: location ft.	true to the best of my knowledge and belief.	
Did any strata contain unusable water? Yes No	(Person, firm or corporation) (Type or print)	
Type of water? depth of strata	Address R. 2 Box 2286 Hermiston	ı, Ore. 97838
Method of sealing strata off	Simula K la (2000)	\sim 1
Was well gravel packed? Tyes No Size of gravel:	[Signed] (Water Well Control	ractor)
Gravel placed from ft. to ft.	Contractor's License No. 419 Date 11	L-8-79 , ₁₉