NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be

filed with the

WATER WELL REPORTE CEIVED

T5X1-3	29E-15
--------	--------

STATE OF OREGON

JAN 1 9 1976

State Well No.

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

(Please type or print)

(Do not write above this WAPFR RESOURCES DEPT.

July 7	DALEM. OREGON
(1) OWNER:	(10) LOCATION OF WELL:
Name Perry Reid	County Umatilla Driller's well number
Address Rt 3/3/4/5/1/	
Herniston, Oregon 47838	14 SE 1/4 Section 15 T. 571 R. 298 W.M.
(2) TYPE OF WORK (check)!	Bearing and distance from section or subdivision corner
New Well Deepening □ Reconditioning □ Abandon □ Reconditioning □ Abandon □	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 40 ft.
Rotary Driven Domestic M Industrial Municipal	Static level 38 ft. below land surface. Date /-1-16
Cable	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded Welded M	(12) WELL LOG: Diameter of well below casing
6 " Diam. from 0 ft. to 74 ft. Gage .257	
ft. Gage ft. Gage	
ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated.
	with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	THERE
perforations from ft. to ft.	Claystone 4 45
perforations from ft. to ft.	Grand 45 74 41B
perforations from ft. to ft.	
(7) SCREENS: Well screen installed? ☐ Yes ☑ No	
Manufacturer's Name	
Type Model No	
Diam Slot size Set from ft. to ft.	
Diam Slot size Set from ft. to ft.	
(O) YURI T MUCHO Drawing in an and make the land in	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? ☐ Yes ☑ No If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs.	
<u> </u>	
" " "	·
(i)h	
Baller test 100 gal./min. with 32 ft. drawdown after / hrs.	
Artesian flow g.p.m.	
Depth artesian flow encountered ft.	Work started /- 5 19 76 Completed /- 7 19 76
(9) CONSTRUCTION;	Date well drilling machine moved off of well /-7 19 76
Well seal—Material used (Lennen)	Drilling Machine Operator's Certification:
Well sealed from land surface to 20 ft.	This well was constructed under my direct supervision.
Diameter of well bore to bottom of sealin.	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal	I am a self
Number of sacks of cement used in well seal	(Drilling Machine Operator)
Number of sacks of cement used in well sealsacks Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons of water	This well was drilled under my jurisdiction and this report is
water ibs./100 gais. Was a drive shoe used? ★ Yes □ No Plugs Size: location ft.	true to the best of my knowledge and belief.
Did any strata contain unusable water? Yes No	Name TROY GRIFFIN (Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address 900 HERMISTON AVE, HERMISTON ORE
Method of sealing strata off	[Signed] (Water Well Contractor)
Was well gravel packed? ☐ Yes 🔀 No Size of gravel:	
Gravel placed from ft. to ft.	Contractor's License No. 65 Date 1-9 , 1976
	•