NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REFORE IVED

STATE OF OREGONOCT 2 3 1975

State Well No. 51/29E-15

(Please type or print)

WATER RESOURCES DEPAte Permit No.

(Do not write above this line)

SALEM, OREGON

(1) OWNER:	(10) LOCATION OF WELL:
Name al Conforth	County /mabella Driller's well number
Address P.O. By 38	14 14 Section 15 T. 571 R. 29 E. W.M.
- 7/madella, (Regon 97882	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check): U	
New Well Deepening □ Reconditioning □ Abandon □	Nation of the Control
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 65 ft.
Rotary Driven Domestic Industrial Municipal	Static level 62 ft. below land surface. Date 6-17.75
Cable	
Dug Borea Migaton & Ical West Guide	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing
10 " Diam. from 0 ft. to 96 ft. Gage .250	Depth drilled 96 ft. Depth of completed well 96 ft.
ft. Gage ft. Gage	Formation: Describe color, texture, grain size and structure of materials;
ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrated,
PERFORATIONS: Perforated? 7 Yes No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
ha : a	
	MATERIAL From To SWL
Size of perforations 1/2 in. by /4 in.	7 opsil - sand 8 6
177 perforations from 70 ft. to 94 ft.	Grilders 6 16 Granel 16 87
perforations from ft. to ft.	0.10
perforations from ft. to ft.	Arce, Charse, round 81 96
(7) SCREENS: Well screen installed? Yes V No	
Manufacturer's Name	
Type Model No.	
Diam, Slot size Set from ft. to ft.	
Diam Slot size Set from ft. to ft.	
(8) WELL TESTS. Drawdown is amount water level is	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? ☐ Yes ▼No If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs.	
" " "	
" " " " " " " " " " " " " " " " " " " "	
Baller test 500 gal./min. with 28 ft. drawdown after hrs.	
Artesian flow g.p.m.	
mperature of water Depth artesian flow encountered ft.	Work started /6-15 1975 Completed /0-17 1975
	Date well drilling machine moved off of well 1975
(9) CONSTRUCTION:	
Well seal—Material used Acutomites	Drilling Machine Operator's Certification: This well was constructed under my direct supervision.
Well sealed from land surface toft.	Materials used and information reported above are true to my
Diameter of well bore to bottom of sealin.	best knowledge and belief.
Diameter of well bore below seal in.	[Signed]
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No/5
Number of sacks of bentonite used in well seal sacks	Drining Machine Operator 2 Zirona 110 Machine 110 Mach
Brand name of bentonite Mattings	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is
of water	true to the best of my knowledge and belief.
Did any strata contain unusable water? Yes No	Name TROY GRIFFIH (Person, firm or corporation) (Type or print)
	Address 900 HERMISTON AVE, HERMISTON OF
ype of water? depth of strata	
thod of sealing strata off	[Signed] (Water Well Contractor)
well gravel packed? Yes No Size of gravel:	, , , , , , , , , , , , , , , , , , ,
el placed from ft. to ft.	Contractor's License No. 65 Date 10-17, 19.7.5