NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER WELL REPORT

STATE OF OREGON

- State	المالا	No	. 5N/2	95	-/	5	
State	W CII	110.			************		

STATE ENGINEER, SALEM, OREGON 97310 RECURIOR Within 30 days from the date

State Permit No.

——————————————————————————————————————	
AL ATTITUDE	(10) LOCATION OF WELL:
MAIER RESOURCES DEP	Tounty Umalila Driller's well number
ddress P.O. Bar 38 SALEM, OREGON	14 14 Section 15 T. 5N. R. 29 E. W.M.
7 malila Oregin 97882	Bearing and distance from section or subdivision corner
2) TYPE OF WORK (check): U	Dearing and distance from section of subdivision corner
Tew Well ☐ Deepening ☑ Reconditioning ☑ Abandon ☐	
f abandonment, describe material and procedure in Item 12.	
	(11) WATER LEVEL: Completed well.
3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found ft.
totary Driven Domestic Industrial Municipal Domestic	Static level 4/6 ft. below land surface. Date /0-3-15
able	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing
" Diam. from ft. to ft. Gage	Depth drilled 12 ft. Depth of completed well 92 ft.
" Diam, from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,
	with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated? Yes \(\text{No.} \)	position of Static Water Level and indicate principal water-bearing strata.
pe of perforator used // illa	MATERIAL From To SWL
Size of perforations /4 in. by //2 in.	in Charse gravel 80 92
120 perforations from 80 ft. to 92 ft.	theepined over
perforations fromft. toft.	and
perforations from ft. to ft.	Suforalu 8"liner
	y v
(7) SCREENS: Well screen installed? Yes No	· · · · · · · · · · · · · · · · · · ·
Manufacturer's Name	
Type Model No	<u> </u>
Diam Slot size Set from ft. to ft.	
Diam Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? ☐ Yes 【No If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs.	
gar, min, with it, drawdown area.	
(1/4	- 40° - 0
Bailer test 3 00 gal./min. with 38 ft. drawdown after 1 hrs.	F The coloning of Control of Cont
Artesian flow g.p.m.	
Temperature of water Depth artesian flow encountered ft.	Work started /0-/ 1975 Completed /0-3 1975
ONSTRUCTION:	Date well drilling machine moved off of well /0-3 19 75
Well seal—Material used Mar disturbed	Drilling Machine Operator's Certification:
	This well was constructed under my direct supervision.
Well sealed from land surface to ft.	Materials used and information reported above are true to my
Diameter of well bore to bottom of seal in.	best knowledge and belief.
Diameter of well bore below seal in.	[Signed] (Driving Machine Operator) Date 19.73
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No. 13
Number of sacks of bentonite used in well seal sacks	
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is
of water	true to the best of my knowledge and belief.
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.	Name TROY GRIFFIM (Person, firm or corporation) (Type or print)
Did any strata contain unusable water? Yes No	(Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address 900 HER MISTONAVE, HERMISTON, ORE.
Method of sealing strata off	[Signed] Water Well Contractor)
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	
	Contractor's License No 65 Date 10-6 1975