NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER WELL REPORTE CEIVED

STATE OF OREGON

AUG 6 1978 ate Well No.

within 30 days from the date of well completion.	STATE		ON 87318 UN 2	ATA
--	-------	--	---------------------	-----

(Do not write above this line) TER RESOURCE & te District No. SN/291-) 144 SALEM CREGON

(1) UWNER:	10) ECCATION OF WELL:				
Name al Conforth	County Umatilla Driller well number				
Address P. O. Bey 38	η Ε 1/4 η Ε 1/4 Section 21 T. 5η. R. 29 Ε, W.M.				
Amabilla Oregon 47882	Bearing and distance from section or subdivis	ion corner	•	·	
(2) TYPĚ OF WORK (check):					
New Well 🔀 Deepening 🗌 Reconditioning 🖫 Abandon 🗔					
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	zell.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 72			ft.	
Rotary Driven Domestic Industrial Municipal	Static level 53 ft. below land	surface. J	Date 1/	29 176	
Cable	Artesian pressure Îbs. per squa	re inch.	Date		
CASING INSTALLED: Threaded Welded 14. Welded 15. Of to 9.5 ft. Gage 12.50 m. Diam. from ft. to ft. Gage	(12) WELL LOG: Diameter of well Depth drilled 95 ft. Depth of comp		- ^	5 ft.	
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and show thickness and nature of each stratu with at least one entry for each change of forms position of Static Water Level and indicate prin	m and aq ation. Repo	uifer pe ort each	enetrated, change in	
· · · · · · · · · · · · · · · · · · ·		- -		swL	
Type of perforator used	MATERIAL	From	To	BWL .	
Size of perforations in. by in.	Topsoil	3.	3		
perforations from ft. to ft.	- Janes	14	<u>14</u> 23		
perforations from ft. to ft.	Boulders 1	23	72	-	
perforations from ft. to ft.	Mul. D	72	95	WiB	
(7) SCREENS: Well screen installed? Yes No Manufacturer's Name	7,43,000	12	7.5	60:15	
Type		1		<u> </u>	
Diam. Slot size Set from ft. to ft.		1			
Diam Slot size Set from ft. to ft.		† †		-	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level					
Was a pump test made? ☐ Yes ❤️No If yes, by whom?		 		<u> </u>	
eld: gal./min. with ft. drawdown after hrs.	1	+ +			
<u>" " " " " " " " " " " " " " " " " " " </u>		1			
<i>n</i> , <i>n</i>		-			
Baller test 700' gal./min. with 37 ft. drawdown after / hrs.					
tesian flow g.p.m.				-	
Temperature of water Depth artesian flow encounteredft.	Work started 7-27 19 16 Complete	ted 7	-2-9	19 76	
(9) CONSTRUCTION:	Date well drilling machine moved off of well		7.29	-	
	Drilling Machine Operator's Certification	•			
Well seal-Material used Bentanite Well sealed from land surface to 28 ft.	This well was constructed under my	direct	super	vision.	
Well sealed from land surface toft. Diameter of well bore to bottom of sealin.	Materials used and information reported best knowledge and belief.	above a	are tru	e to my	
Diameter of well bore to bottom of seal		// -Date	7-26	1, 1976	
	(Drilling Machine Operator)			, 19/7	
Number of sacks of cement used in well sealsacks Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No.	66	5		
Brand name of bentonite					
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:				
of waterlbs./100 gals.	This well was drilled under my jurisd true to the best of my knowledge and be		nd this	report is	
Was a drive shoe used? Yes □ No Plugs Size: location ft.		.1761.			
Did any strata contain unusable water? Yes No	Name TROY GPIFFIM (Person, firm or corporation),	(T ₃	pe or pr	int)	
Type of water? depth of strata	Address 900 HERMISTINORE	HERA	1157	CH OPE	
Method of sealing strata off	Trave Mais	1/2	~		
Was well gravel packed? ☐ Yes ¼ No Size of gravel:	[Signed] (Water Well John	tractor)			
Gravel placed from ft. to ft.	Contractor's License No		29	1976	
Carros proced from minimum for the to minimum for	1 Contractor of Antonio 110			,	