NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT. SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

UMAT State Well No. 5N 29F - 2Lad C

(1) OWNER:	(10) LOCATION OF WELL:
Name CL-2 FARMS	County Umatilla Driller's well number
Address $R + 3 B_{0} \times 3734B$	SW 14 SE 14 Section 26 T. 51 R. 29E W.M.
Herris bon, OR 97838	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well Deepening Reconditioning Abandon	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 283 ft.
Rotary Driven Domestic Industrial Municipal Cable Jetted	Static level 76 ft. below land surface. Date 9-3-80
Cable Jetted Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date
(5) CASING INSTALLED: Threaded Welded - Welded - 106 ft. Gage 20	(12) WELL LOG: Diameter of well below casing 8
	Depth drilled 385 ft. Depth of completed well 385 ft.
ft. toft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,
	with at least one entry for each change of formation. Report each change in
(6) PERFORATIONS: Perforated? ☐ Yes ☑ No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	SAND 0 3
perforations from ft. to ft.	Brown Clan & Hack Bosalt 3 100
perforations from ft. to ft.	8/Ach Bosalf 106 203
perforations from ft. to ft.	(Rep Bores Boalt 203 250 H,0
(7) SCREENS: Well screen installed? [] Yes [] Wo	B/Ach Basal 250 256
(7) SCREENS: Well screen installed? Yes Name Manufacturer's Name	KED Boros Besalt yellow Tale 256 319 14,0
Type Model No	Black Book 3/9 339
Diam. Slot size Set from ft. to ft.	Black Basalt grow TATE 339 346
Diam Slot size Set from ft. to ft.	Black Bosal grow TAC 346 383 14,0
	363 307
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	DECEMEN
Was a pump test made? Yes ho If yes, by whom?	KLULIVLU
y	OCT 0 1 1980
и и и	l
н н н	WATER RESOURCES PEPT
Bailer test gal./min. with ft. drawdown after hrs.	SALEM, OREGON
an flow g.p.m.	
Temperature of water 64 Depth artesian flow encountered ft.	Work started Day 28 1980 Completed Sager 3 1980
(9) CONSTRUCTION:	Date well drilling machine moved off of well Syst 3 19 &c
Well seal-Material used PORTLAND CRMON	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my
Diameter of well bore to bottom of sealin.	best knowledge and belief.
Diameter of well bore below seal	[Signed] / All / Date 9-12 1980
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)
How was cement grout placed? DunpED	Drilling Machine Operator's License No
	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? 🗗 Yes 🛘 No Plugs Size: location ft.	true to the best of my knowledge and belief.
Did any strata contain unusable water? 🗌 Yes 🗘 No	(Person, firm or corporation)) (Type or print)
Type of water? depth of strata	Address Al Box 19 / Lot Lock Ca
Method of sealing strata off	Jan 1/2
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	[Signed] (Water Well Contractor)
Gravel placed fromft. toft.	Contractor's License No. 759 Date 9-12 1980
erarer placed from	Contractor's License No