NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be

STATE ENGINEER, SALEM, OREGON 97310 37 17 of well completion.

WATER WELL REPORT NOV6 1974 Well No. 5/

(Please type or print) STATE ENGINEER State Permit No.

(Do not write above this line) SALEM, OREGON

(1) OWNER:	(10) LOCATION OF WELL:
Name Windell a Grass	County Umatilla Driller's well number
Address Bex 144	14 14 Section 28 T. 571. R. 298. W.M.
Powell Buile, Oregon 97753	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check): U	
New Well 🗗 Deepening 🗌 Reconditioning 🗍 Abandon 🗎	100 T
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 114 ft.
Rotary Driven Domestic M Industrial Municipal	Static level 40 ft, below land surface. Date $\langle 0/30/74 \rangle$
Cable	
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing 6"
O	Depth drilled 175 ft. Depth of completed well 175 ft.
	Formation: Describe color, texture, grain size and structure of materials;
"Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrated,
PERFORATIONS: Perforated? Yes Yes	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	Sand aras 09
perforations from ft. to ft.	9 14
perforations fromft. toft.	Beach 14 103
perforations from ft. to ft.	Basalt, Land grave 103 114
	Rock brown. 114 123 W.B.
(7) SCREENS: Well screen installed? Yes No	Rock, med, splack 123 148
Manufacturer's Name	Rock brown 148 159
Type Model No.	Rick, hed 159 175 W.B.
Diam. Slot size Set from ft. to ft. Diam. Slot size Set from ft. to ft.	
Diani. Stot size Set Hom 11. to	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? ☐ Yes ▼No If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs.	
" " " " " " " " " " " " " " " " " " "	1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
ark	
Baffer test /6 / gal./min. with //6 ft. drawdown after i hrs.	A Company of the Comp
Artesian flow g.p.m.	
perature of water Depth artesian flow encountered ft.	Work started /0 - 28 1974 Completed /6-3d 1974
(9) CONSTRUCTION:	Date well drilling machine moved off of well 10-30 1974
Well seal-Material used Cennand	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my
Diameter of well bore to bottom of seal	best knowledge and belief.
Diameter of well bore below seal in.	[Signed] Lanca Totale Date 11-1, 1974
Number of sacks of cement used in well seal sacks	Drilling Machine Operator) Drilling Machine Operator's License No. 665
Number of sacks of bentonite used in well seal sacks	Dilling Machine Operator & Intense 110.
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is
of waterlbs./100 gals. Was a drive shoe used? Noves I No Plugs Size location #	true to the best of my knowledge and belief.
Was a drive shoe used?	Name TROY GRIFFIH (Person, firm or corporation) (Type or print)
	(Person, firm or corporation) (Type or print) Address 90.0 HERMISTON ANE, HERMISTON ORE.
	TAMESO LECTION AND LANGUAGE PARTY AND LANGUAGE PART
Method of sealing strata off	[Signed] The Man Well Charles and Charles
Was well gravel packed? ☐ Yes KNo Size of gravel:	Contractor's License No. (2 Date //-/ 10.74
Gravel placed from ft. to ft.	Contractor's License No. 65 Date 1979