WATER WELL REPORT

STATE OF OREGON



REGEIVED. State Well No.

MAR 29 1984

PLEASE TYPE or REMTER INKSOURCES DEPT. SALEM. OREGON

(1) OWNER:	(10) LOCATION OF WELL:
Name Charles H. Bloodsworth	County Unatilla Driller's well number
Address Rt. 2 Box 2801	S 4 S W 4 Section 31 T. 5 R. 29 W.M.
City Hermiston State Or 97838	Tax Lot # Lot Blk Subdivision
(2) TYPE OF WORK (check):	Address at well location: Rt. 2, Box 280
New Well	Hermiston, Or 97838
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 25 ft.
	Static level 22 ft. below land surface. Date 3-9-84
Rotary Air Driven	Artesian pressure lbs. per square inch. Date
☐ Bored ☐ Thermal: Withdrawal ☐ Reinjection ☐	(12) WELL LOG: Diameter of well below casing
(5) CASING INSTALLED: Steel Plastic	Depth drilled /85 ft. Depth of completed well /85 ft.
Threaded Welded	Formation: Describe color, texture, grain size and structure of materials; and show
12" Diam. from	thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level
	and indicate principal water-bearing strata.
LINER INSTALLED:	MATERIAL From To SWL
	Sandy=9011 04
(6) PERFORATIONS: Perforated? Yes No	Sand 4 77 (1) R
Type of perforator used	Grey clay 7780
Size of perforations in. by in.	Fine sknd 8085
perforations fromft. toft.	Grave/ 8586
	Grey 19252/f 86 151
perforations from ft. to ft.	POTOUS grey basalt 151 181 WB
(7) SCREENS: Well screen installed? Yes No	Broken grey basalt 181 185 WB
Manufacturer's Name	
Type Model No.	
Diam. Slot Size Set from ft. to ft.	1
Diam. Slot Size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
below static level	The state of the s
Was a pump test made? ☐ Yes Woo If yes, by whom?	1000
d: gal./min. with ft. drawdown after hrs.	
100	
satier test gal/min. with ft. drawdown after hrs. Artesian flow g.p.m.	
perature of water Depth artesian flow encountered ft.	
(A) CONCERTICATION	Work started 3-5 19 7 Completed 3 1974
9) CONSTRUCTION: Special standards: Yes No Well seal—Material used	Date well drilling machine moved off of well 3-9 19 84
Well sealed from land surface to	(unbonded) Water Well Constructor Certification (if applicable):
Diameter of well bore to bottom of seal	This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal	[Signed]
Number of sacks of cement used in well seal sacks	
low was cement grout placed? Pressure grouted	Bonded Water Well Constructor Certification Hutomobile Ins. Co. Bond SB 36090 Issued by: Oregon Hutomobile Ins. Co.
J	(number) Surety Company Name
A -	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Vas pump installed?	Name Wallace Drilling
Vas a drive shoe used?	(Person, firm or corporation) (Type or print)
Did any strata contain unusable water?	Address 1307 SW23rd, Pendleton, Or. 97801
Aethod of sealing strata off	[Signed] Latrick C Wallacl
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	Water Well Constructor Date
Gravel placed from	Date, 198, 198