

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT,

SALEM, OREGON 97310

within 30 days from the date of well completion.

RECEIVED WATER WELL REPORT STATE OF OREGON

OCT 28 1977

(Please type or print)

(Do not write above this line)

WATER RESOURCES DEPT.

UMAT 3843

State Well No. 5N/29E-34

APP State Permit No. G-14119

(1) OWNER: SALEM, OREGON

Name Mon McEwen
Address Rt. 3 Box 3724
Hermiston, Oregon 97838

(2) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon []
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [X] Driven []
Cable [] Jetted []
Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [X] Industrial [X] Municipal []
Irrigation [] Test Well [] Other []

CASING INSTALLED:

Threaded [] Welded [X]
8" Diam. from 0 ft. to 22 ft. Gage 250

PERFORATIONS:

Perforated? [] Yes [X] No
of perforator used
Size of perforations in. by in.

(7) SCREENS:

Well screen installed? [] Yes [X] No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? [] Yes [X] No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.

(9) CONSTRUCTION:

Well seal—Material used Cement
Well sealed from land surface to 22 ft.
Diameter of well bore to bottom of seal 11 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal 8 sacks
How was cement grout placed?
Was a drive shoe used? [X] Yes [] No Plugs Size: location ft.
Did any strata contain unusable water? [] Yes [X] No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? [] Yes [X] No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Umatilla Driller's well number
N.W. 1/4 N.E. 1/4 Section 34 T. 5N. R. 29E. W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 152 ft.
Static level 150 ft. below land surface. Date 10-14-77
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 8"
Depth drilled 428 ft. Depth of completed well 428 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Rows include Topsoil, Sand, Sand + gravel, Claystone, light brown, Rock, black, Rock, red + brown, Basalt, black, Rock, brown, Rock, black, Rock, brown, Rock, black + green, Rock, blue + black, Rock, green + red, Basalt, black.

Work started 10-11 1977 Completed 10-14 1977
Date well drilling machine moved off of well 10-14 1977

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] [Signature] Date 10-17, 1977
Drilling Machine Operator's License No. 1027

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name TROY GRIFFIN
Address 900 HERMISTON AVE. HERMISTON ORE
[Signed] [Signature]
Contractor's License No. 65 Date 10-17, 1977