NO WATER WELL CONFECTOR E INF N e original and first correction of this report are to be APR 6 - 1972	L REPORT
filed with the AIRO 1972 STATE OF STATE ENGINEER, SALEM, OREGON STATE ENGINEER stype within 30 days from the datSALEM. OREGONAt write all of well completion.	
X (1) OWNER: Name City of Millow FREEWATER	(10) LOCATION OF WELL: County Umatilla Driller's well number
Address PD, BOX 108 Milton FRUTR. ORE	NE 14 5W 14 Section 2 T. 5N R. 35 E W.M.
97862	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well 🔲 Deepening 🔲 Reconditioning 🔀 Abandon 🗆	586°44'41 527' FROM Ctr. Sec.
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	
Potomy D Driven Ci	Depth at which water was first found ft.
Cable Z Jetted D Domestic D Industrial Municipal Z	
Dug 🔲 Bored 🗌 🔤 Irrigation 🗋 Test Well 🔲 Other 🔲	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded □ Welded X 12" Diam. from + 1	(12) WELL LOG: Diameter of well below casing 12. Depth drilled 915 ft. Depth of completed well 915 ft.
ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials;
	and show thickness and nature of each stratum and aquifer penetrated,
PERFORATIONS: Perforated? [] Yes KNo.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	
Harris Barnett, , , , , international and a state of the state of the second of the se	arr Dockle o 1 wd
perforations from	SEE PREVIOUS hold
ft. toft.	
(7) SCREENS: Well screen installed? Ves X No	
Manufacturer's Name	
TypeModel No.	
Diam Slot size	
Diam Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? X Yes I No If yes, by whom?	
Vield: 1.500 gal./min. with 145ft. drawdown after 10 hrs.	
// // // // // // // // // // // // //	
	·····
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	
reperature of water 60 Depth artesian flow encountered ft.	Work started 12-6 1971 Completed 2-29 1972
(9) CONSTRUCTION:	Date well drilling machine moved off of well $2 - 25$ 1972
Well seal-Material used 12" CASING, CEMENT	Drilling Machine Operator's Certification:
Well sealed from land surface to 232'	This well was constructed under my direct supervision.
Diameter of well bore to bottom of seal in.	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal	
Number of sacks of cement used in well seal 2.50 sacks	[Signed] [Drilling Machine Operator) Date
Number of sacks of bentonite used in well seal	Drilling Machine Operator's License No. 36
Brand name of bentonite	
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:
of water	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? Xes D No Plugs Size: location ft.	Allow to the additional and
Did any strata contain unusable water? 🔲 Yes 💢 No	Name (Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address 115 REES AVE. W. W. WASH.
Method of sealing strata off	
	[Signed]
Gravel placed from ft. to ft.	Contractor's License No. 2, 36 Date 3-30, 1972
(USE ADDITIONAL SE	HEETS IF NECESSARY) SP*45656-119

- ----