NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT B 2 5 1966

STATE OF OREGON TE ENGINEER (Please type or print) ALEM OREGONALE Permit No. ...

(1) OWNER:	(11) WELL TESTS: Drawdown is amount water level is lowered below static level	
Name July 1	Was a pump test made? Yes \(\subseteq \text{No If yes, by whom?} \)	
Address 12/4 Sung Ur	Yield: 300 gal./min. with 7/ ft. drawdown	after hrs.
estige place " work.	n n . n .	
(2) LOCATION OF WELL:	" " "	
County / Driller's well number	Bailer test gal./min. with ft. drawdow	n after hrs.
NW 1/2 No 1/2 Section 24 T.6N R. 33 EW.M.	Artesian flow g.p.m. Date	
Bearing and distance from section or subdivision corner	Temperature of water Was a chemical analysis ma	ide? Yes No
1000#4	(12) WELL LOG: Diameter of well below casi	ng
From NW enry See 24 a distance	Depth drilled 230 ft. Depth of completed well	230 ft.
1305 5 44° W to existing well, there	Formation: Describe by color, character, size of material show thickness of aquifers and the kind and nature of the	
5/7' · 558° 42' W.	show thickness of aquifers and the kind and nature of the stratum penetrated, with at least one entry for each cha	e material in each inge of formation.
(3) TYPE OF WORK (check):		FROM TO
	TOP SOIL	1 1 1 2 2
	CLAY-Gravel Bluish	105 132
bandonment, describe material and procedure in Item 12.	Clay	32 134
(4) PROPOSED USE (check): (5) TYPE OF WELL:	cement Gravel	34 188
Domestic Industrial Municipal Rotary Driven	SOND + GHOVEL	88 203
Irrigation Test Well Other Cable Jetted	Cray + Graver	103 250
Dug [] Bored []		
(6) CASING INSTALLED: Threaded Welded	·	
(7) PERFORATIONS: Perforated? Yes No		
//		
Type of perforator used Hand COICh		
Size of perforations 3/16 in. by 5 in		
-		
perforations fromft. toft.		
perforations from ft. to ft.		
perforations from ft. to ft.		
(8) SCREENS: Well screen installed? ☐ Yes ☐ No		
Manufacturer's Name		
<u>Type</u> Model No		
n	Work started DEC, 3 1956 Completed	7H 9 195
Diam. Slot size Set from ft. to ft.	Date well drilling machine moved off of well	19
(9) CONSTRUCTION:	(13) PUMP:	
	Western Rung	1.
Well seal—Material used in seal	Manufacturer's Name	<u></u>
Depth of seal ft. Was a packer used?	Type: VIIII H	P. 30
Diameter of well bore to bottom of sealin.	Water Well Contractor's Certification:	
Were any loose strata cemented off? Yes No Depth		
Was a drive shoe used? ☐ Yes ☐ No	This well was drilled under my jurisdiction at true to the best of my knowledge and belief.	ad this report is
Was well gravel packed? ☐ Yes ☐ No Size of gravel:		05
Gravel placed from ft. to ft.	NAME (Person firm or corporation) (Type	e or print)
Did any strata contain unusable water? Yes No	NAME HEITSTUMAN BY (Person, firm or corporation) Address MILTON - Freewatte	Er, ORK
Type of water? depth of strata	PAULI COS . R. F. F. F. F. W. W. S. S	
Method of sealing strata off	Drilling Machine Operator's License No. A.	76
(10) WATER LEVELS:	I am a Collisad How Takes	man
Static level 78,5 ft. below land surface Date Jan. 9	[Signed] (Water Well Contracts)	700-7
Artesian pressure lbs. per square inch Date	Contractor's License No Date	22 10/1
The state of the s	1 Constactor o Incense No Date Date	, 19.M.M