| Name John L. Richartz | (II) LOCATION OF WELL: | | |
|--|---|--|----------------------------|
| ** | County Um a 75/4. Driller's well n | | |
| Address RT. 2 Millon Freewaten Ore. | E 12 No 1/2 N W stytion 24 T. Co | | _ W.M. |
| (2) TYPE OF WORK (check): | Bearing and distance from section or subdivision | " | |
| New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐ | N.30° W 2305 A. | from Ject | 104 |
| If abandonment, describe material and procedure in Item 12. | center #24 | | |
| (3) TYPE OF WELL: (4) PROPOSED USE (check): | | | |
| Rotary Driven Demostic Demostic Demostic | (12) WELL LOG: Diameter of well | below casing | 0 |
| Cable | Depth drilled 35 ft. Depth of comp | oleted well 3 | <u>ft.</u> |
| | Formation: Describe color, texture, grain size | | |
| CASING INSTALLED: Threaded Welded | and show thickness and nature of each strate with at least one entry for each change of form | | |
| 10 " Diam. from 0 ft. to 35 ft. Gage . 250 | in position of Static Water Level as drilling pr | oceeds. Note drill | ing rates. |
| " Diam, fromft. toft. Gage | MATERIAL | From To | SWL |
| " Diam. fromft. toft. Gage | | · · · · · · · · · · · · · · · · · · · | 3 1/ |
| PERFORATIONS: Perforated? Pres D No. | Dag well 10 18. | *** | 3/2 |
| Type of perforator used AceTylene | Mada Water Danier | 18 23 | 21/2 |
| Size of perforations /2 in. by 8 in. | Med Water Bearing | 10 ×3 | J/2 |
| perforations from | Qravel | 1. | - |
| perforations from 20 ft. to ft. | Fine Black Sand | 23 35 | 3 1/2 |
| perforations from ft. to ft. | 7-11-1 | | |
| perforations from ft. to ft. | | | |
| perforations fromft. toft. | | | |
| (7) SCREENS: Well screen installed? Yes Pro | | | |
| Manufacturer's Name | | | |
| Type Model No. | | + | |
| Diam Slot size Set from ft. to ft. | | + - 1 | - |
| Diam. Slot size Set from ft. to ft. | | | <u> </u> |
| (8) WATER LEVEL: Completed well. | | | |
| Static level 3 1/2 ft. below land surface Date March. 14 | | | Ī, |
| esian pressure i lbs. per square inch Date | 7: | 1. | |
| | | | |
| (9) WELL TESTS: Drawdown is amount water level is lowered below static level | | | |
| Was a pump test made? Yes PNo If yes, by whom? | - N | | / / 6 |
| d: 80 gal./min. with 6 ft. drawdown after 24 hrs. | Work started March 12 1968 Comple | | 1968 |
| owner's "dentrifugal "pump, " | Date well drilling machine moved off of well | Merch 15 | 19 6 8 |
| " Maych 29-30-68" | Drilling Machine Operator's Certification: | | |
| Bailer test None gal./min. with ft. drawdown after hrs. | This well was constructed under my drials used and information reported abo | irect supervision | . Mate- |
| Artesian flow g.p.m. Date | knowledge and belief. | 1 1 | |
| Temperature of water Was a chemical analysis made? Was a Chemical analysis made? Was a Chemical analysis made? | [Signed] Lowell Tr. Muslett | Date March | <u> 15₁₉ 68</u> |
| (10) CONSTRUCTION: | (Drilling Machine Operator) | 1/ | |
| Well seal—Material used BenToniTe | Drilling Machine Operator's License No. | | |
| Depth of seal 18 Billon & F Dug Well ft. | Water Well Contractor's Certification: | | |
| Diameter of well bore to bottom of seal 48 in. | This well was drilled under my jurisd | liction and this | report is |
| Were any loose strata cemented off? Yes No Depth | true to the best of my knowledge and bel | | - |
| Was a drive shoe used? ☐ Yes ☐ No | NAME LOW LI W. Manie 17 | (Type or print |) |
| Did any strata contain unusable water? Yes | RT# 5 Party M Min | ton Frezui | ton A. |
| Type of water? depth of strata | Address Vol. & Boy // Fi Mill | AII | 10201 |
| Method of sealing strata off | [Signed] Lowell The Mark | latt. | |
| Was well gravel packed? [] Yes 1240 Size of gravel: | (Water Well Contra | actor) | |
| Gravel placed fromft. toft. | Contractor's License No. 265 Date | Merch 15 | 19.68 |