

STATE OF OREGON

(Please type or print)

(Do not write above this line)

RECEIVED

APR 5 - 1978

State Well No.

State Permit No

SALEM, OREGON

Name Raymond R. Fricke
Address Rt. - 3 - Box 129L
Milton-Freewater, Oregon

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

Rotary ☐ Driven ☐ Domestic ☐ Industrial ☐ Municipal ☐
 Cable ☒ Jetted ☐ Irrigation ☒ Test Well ☐ Other ☐
 Bored ☐

Threaded ☐ Welded ☒

6" Diam. from 0 ft. to 85 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

Perforated? ☐ Yes ☒ No.

Type of perforator used			
Size of perforations		in. by	in.
..... perforations from	 ft. to		 ft.
..... perforations from	 ft. to		 ft.
..... perforations from	 ft. to		 ft.

Well screen installed? ☐ Yes ☒ No

Manufacturer's Name _____

Type _____ Model No. _____

Diam. _____ Slot size _____ Set from _____ ft. to _____ ft.

Diam. _____ Slot size _____ Set from _____ ft. to _____ ft.

Drawdown is amount water level is lowered below static level

Was a pump test made? ☐ Yes ☒ No If yes, by whom?

Qtd:	gal./min. with	ft. drawdown after	hrs.
"	"	"	"
"	"	"	"
Bailer test	20 gal./min. with	2 ft. drawdown after	1 hrs.
Artesian flow	g.p.m.		
Temperature of water	54	Depth artesian flow encountered	ft.

Well seal—Material used Puddled clay

Well sealed from land surface to 20 ft.

Diameter of well bore to bottom of seal 9 $\frac{1}{2}$ in.

Diameter of well bore below seal 7-3/8 in.

Number of sacks of cement used in well seal _____ sacks

Number of sacks of bentonite used in well seal 1 $\frac{1}{2}$ sacks

Brand name of bentonite Volclay

Number of pounds of bentonite per 100 gallons

of water 75 lbs./100 gals.

Was a drive shoe used? ☒ Yes ☐ No Plugs _____ Size: location _____ ft.

Did any strata contain unusable water? ☐ Yes ☒ No

Type of water? _____ depth of strata _____

Method of sealing strata off _____

Was well gravel packed? ☐ Yes ☒ No Size of gravel: _____

Gravel placed from _____ ft. to _____ ft.

County Umatilla Driller's well number _____
 _____ $\frac{1}{4}$ _____ $\frac{1}{4}$ Section 14 T. 6N R. 35 E W.M. _____
 Bearing and distance from section or subdivision corner _____

Depth at which water was first found 41 ft.

Static level 35 ~~XX~~ ft. below land surface. Date 3/7/76

Artesian pressure _____ lbs. per square inch. Date _____

Diameter of well below casing 6"

Depth drilled 90 ft. Depth of completed well 90 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

[illegible]

Work started 3/2 19 76 Completed 3/25 19 76
Date well drilling machine moved off of well 3/29 19 76

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] E M G Behrum Date 4/2, 1976.
(Drilling Machine Operator)

Drilling Machine Operator's License No. 124

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name E. M. J. Behrens
(Person, firm or corporation) (Type or print)

Address Rt. 4 - Box 21-Milton-Freewater, Ore

[Signed] E M J Behrm
(Water Well Contractor)

Contractor's License No. 229 Date 4/2 19 76