NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the
STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date of well completion.

UMAT 4226

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

RECEIVED APR 5 - 1976 WATER RESOURCES DEPT. SALEM, OREGON

State Well No. 6N/35E-14
State Permit No.

(1) OWNER:
Name John L. Packard
Address Box 143
Milton-Freewater, Oregon

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Bored ☐

(4) PROPOSED USE (check):
Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(5) CASING INSTALLED: Threaded ☐ Welded ☒
6" Diam. from 0 ft. to 65 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS: Perforated? ☐ Yes ☒ No.
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☒ Yes ☐ No If yes, by whom? Driller
Yield: 15 gal./min. with 0 ft. drawdown after 1 hrs.
" " " "
" " " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water 54 Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used Puddled clay
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 9½ in.
Diameter of well bore below seal 7-3/8 in.
Number of sacks of cement used in well seal sacks
Number of sacks of bentonite used in well seal 1½ sacks
Brand name of bentonite Volclay
Number of pounds of bentonite per 100 gallons of water 75 lbs./100 gals.
Was a drive shoe used? ☒ Yes ☐ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Umatilla Driller's well number
¼ ¼ Section 14 T. 6N R. 35 E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 39 ft.
Static level 34 ft. below land surface. Date 2/23/76
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 6"
Depth drilled 74 ft. Depth of completed well 74 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. *Report each change in position of Static Water Level and indicate principal water-bearing strata.*

MATERIAL	From	To	SWL
Gray clay & fine sand	0	24	
Gray clay & med. gravel	24	39	
Sm. Boulders & gray clay	39	68	33
Tan clay	68	72	33
Small boulders	72	74	19

Work started 2/18/76 Completed 3/1 1976
Date well drilling machine moved off of well 3/1 1976

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] E M J Behrens Date 4/2, 1976
(Drilling Machine Operator)
Drilling Machine Operator's License No. 124

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name E. M. J. Behrens
(Person, firm or corporation) (Type or print)
Address Rt.4-Box 21-Milton-Freewater, Oreg.
[Signed] E M J Behrens
(Water Well Contractor)
Contractor's License No. 229 Date 4/2, 1976

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119