WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON within 30 days from the date of well completion.



WATER WELL REPORT

SP*45656-119

STATE OF OREGON MAR 1 1974 State Well No. (Please type or print) STATE ENGINEER Permit No. (Do not write above this line ALEM, OREGON

(1) OWNER:	(10) LOCATION OF WELL:		
Name Jerry Dirson Robert A. Dixson	County Um atila Driller's well number		
Address Address Lowden Wash		R.	W,M.
million contains 4786		•	£
(2) TYPE OF WORK (check):	Bearing and distance from section of subdivision	i comer	
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐		F 4 4 7 7 7 7	¥-
If abandonment, describe material and procedure in Item 12.		11	
	(11) WATER LEVEL: Completed we	:11.	-
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	<u> </u>	ft
Rotary Driven Domestic Industrial Municipal Domestic Municipal Domestic	Static level 98 ft. below land su	irface. Date	4.22-7
Cable Defted Dug Bored Trigation Test Well Other	Artesian pressure Ibs. per square	inch. Date	4
(3) CASING INSTALLED: Threaded Welded Welded	(12) WELL LOG: Diameter of well below casing		
10 "Diam from 0 ft. to 3/6 ft. Gage 1200	Depth drilled 285 ft. Depth of comple	ted well 24	, 9 ft.
" Diam. fromtt. Gage	Formation: Describe color, texture, grain size a	nd structure of m	aterials;
" Diam. from ft. Gage	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in		
PERFORATIONS: Perforated? 12-Yes No. 73	position of Static Water Level and indicate princ	ipal water-bearin	g strata.
Type of perforator used Mills 89 = 232 - Hecty/enc 3	MATERIAL	From To	SWL
7/ 3	0	0 63	
Size of perforations / j in. by j in.	Stop Soil & Brown Clay	63 78	
perforations from 89 ft. to	Gravel - Med Coane (Brown)	78 87	29
(O perforations from 100 ft. to 144 ft.	Med Gravel Cleaner		<u> </u>
	lossially some water	87 101	37
(7) SCREENS: Well screen installed? ☐ Yes Deno	Gravel-CemenTed · Rypun	101 144	
Manufacturer's Name	Clave Brown	144 147	
Type Model No.	Gravel with Brown Clay.		-5.5
Diam. Slot size Set from ft. to ft.	* Med-come Sand S. W.L. P.	Fring 197 189	94
Diam Slot size Set from ft. to ft.	General with Bridge Clay		
	Clay - Brown	189. 191	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Gravel-Pea gravel Cement	ed l	
Was a pump test made? Eves □ No If yes, by whom?	in Brown Llay	191 248	•
ad: 355 gal./min. with 130 ft. drawdown after 6 hrs.	Brown Clay	248 250	·
	Brown clay mixed with		· · · · · · · · · · · · · · · · · · ·
" " " " " " " " " " " " " " " " " " "	Coance Sand - pea Gravel	250 271	48
	Brown Clay	211 273	
Bailer test gal./min. with ft. drawdown after hrs.	GUAYEL CEMENT Brown	273 298	
Artesian flow g.p.m.	BLOWL CLAY	2981302	<u> </u>
iperature of water 56Depth artesian flow encountered ft.	Work started Pec, 17 1973 Complete	a 1901.21	19 /4
(9) CONSTRUCTION:	Date well drilling machine moved off of well	JA4. 23	19 7 4
Well seal-Material used RenToniTe	Drilling Machine Operator's Certification:		
Well sealed from land surface to 43 ft.	This well was constructed under my Materials used and information reported	direct super	vision.
Diameter of well bore to bottom of sealin.	best knowledge and belief.	above are nue	to my
Diameter of well bore below seal in.	[Signed] Lowell M. Marlatt	Date 12.22	2 1973
Number of sacks of cement used in sell seal sacks	(Drilling Machine Operator)	9 j	.,
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No.	//	
Brand name of bentonite	West of West Control Confession		•
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:		
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Was a drive shoe used? Tes 🗆 No Plugs Size: location ft.	Name Lowell W. MariaTT		
Did any strata contain unusable water?	(Person, firm or corporation)	(Type or pri	
Type of water? Sand Freenth of strata 43-78'	Address KI # 3 BOX 11174	Millon	rcewa
Method of sealing strata off Co.sed Out.	reignal Lowell Willand	ett.	
Was well gravel packed? ☐ Yes ☑ No Size of gravel:	[Signed] (Water Well Contr	actor)	
Gravel placed from ft. to ft.	Contractor's License No. 265 Date	don. 22	, 197.4

(USE ADDITIONAL SHEETS IF NECESSARY)

THE TO. WATER WELL CONTRACTOR. The original and first copy of this report are to be filed with the

E ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORRECEIVED

SALEM ORFGON

(1) OWNER:	(10) LOCATION OF WELL:		
Name	County Driller's well number		
Address	¼ ¼ Section T. R. W.M.		
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner		
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐			
If abandonment, describe material and procedure in Item 12.			
	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found ft.		
Rotary Driven Domestic Industrial Municipal	Static level ft. below land surface. Date		
Bored Irrigation Test Well Other	Artesian pressure Ibs. per square inch. Date		
CACTAGO TATOMATA TATA	por square men. Sacc		
5) CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing		
"Diam. from ft. to ft. Gage	Depth drilled ft. Depth of completed well ft.		
ft. toft. Gage			
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,		
DEDENOD A MYONG	with at least one entry for each change of formation. Report each change in		
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate principal water-bearing strata.		
Type of perforator used	MATERIAL From To SWL		
Size of perforations in. by in.	CEMENT GLAVEL . Brown)		
perforations from ft. to ft.	with Thin streets		
perforations from ft. to ft.	possiably water. 302 334		
perforations from ft. to ft.	Brown Clay 334 341		
	Tan clay 34/358		
(7) SCREENS: Well screen installed? Yes No	Corovel Med-Fine Brown 358 361		
Manufacturer's Name			
Type Model No.			
Diam Slot size Set from ft. to ft.			
Diam			
in the second se			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
Was a pump test made? ☐ Yes ☐ No If yes, by whom?	x 100 2 2 2 2		
d: gal./min. with ft. drawdown after hrs.	The same of the sa		
n H n			
и и и			
Bailer test gal./min. with ft. drawdown after hrs.			
	a		
	72-22 22		
perature of water Depth artesian flow encountered ft.	Work started 19 Completed 19		
(9) CONSTRUCTION:	Date well drilling machine moved off of well 19		
Well seal—Material used	Drilling Machine Operator's Certification:		
	This well was constructed under my direct supervision.		
Well sealed from land surface toft.	Materials used and information reported above are true to my		
Diameter of well bore to bottom of sealin.	best knowledge and belief.		
Diameter of well bore below sealin.	[Signed] Date, 19		
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No.		
Number of sacks of bentonite used in well seal sacks	Ditting Wachine Operator's Incense No.		
Brand name of bentonite	Water Well Contractor's Certification:		
Number of pounds of bentonite per 100 gallons	-		
f water lbs./100 gals.	I will to me pest of the knowledge and benen.		
Was a drive shoe used? 🗌 Yes 🖺 No Plugs Size: location ft.			
Old any strata contain unusable water? Yes No	(Person, firm or corporation) (Type or print)		
Type of water? depth of strata	Address		
Follow Fig. 1. A section of the sect	and a second sec		
	[Signed] (Water Well Contractor) Contractor's License No. Date 10		
Vas well gravel packed? ☐ Yes ☐ No Size of gravel:	(water well Contractor)		
Gravel placed from ft. to ft.	Contractor's License No Date 19		