NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date
of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

*UMAT 4294

State Well No. 6N/35E-19bd
State Permit No.

(1) OWNER:	(10) LOCATION OF WELL:
Name Ruth & Paea Grav	TT I A T T
Address Route 2 Box 43	CIP MILI
Walaa Walla, WA 99362	W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner
New Well Deepening Reconditioning Abandon	
If abandonment, describe material and procedure in Item 12.	(11) ****
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.
Rotary & Driven C	Depth at which water was first found 75
Cable ☐ Jetted ☐ Domestic ☐ Industrial ☐ Municipal ☐ Irrigation ☑ Test Well ☐ Other	Date 1 22 UV
	Artesian pressure lbs. per square inch. Date
(5) CASING INSTALLED: Threaded Welded M	(19) WELL LOG
16 "Diam. from +2 ft. to 18 ft. Gage •250 12 "Diam. from +2 ft. to 67 ft. Gage •250	(12) WELL LOG: Diameter of well below casing 12"
12 "Diam from +2 ft. to 67 ft. Gage •250	Depth drilled 400 ft. Depth of completed well 400 ft.
"Diam. from ft. to 400 ft. Gage .250	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each other.
(6) PERFORATIONS:	
remorated? - Yes No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used torch Size of perforations 1/8 in. by in.	MATERIAL From To SWL
400 perforations from 300 /100	soil 0 6
60 It. W	gravel 6 10
40 195 205	yellow clay&brown basalt 10 75 broken basalt 25 85 H20
40	10 0 1120
(7) SCREENS: Well screen installed? West Screen installed? Yes No	hmolron har-14
Manufacturer's Name	175 200 1120
Type Model No.	broken basalt 270 285 H20
Diam. Slot size Set from ft. to ft.	brown clay & black basalt 285 300
Diam. Slot size Set from ft. to ft.	broken basalt & yellow talc 300 400 H20
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? \(\tilde{\tilde	DECEMEN
360	VECTIAFD
gal/min. with 200 ft. drawdown after 1 hrs.	AUG 1 1980
11	WATER RESOURCES DEPT
The second secon	SALEM, OREGON
hrs.	BALEM, UREGUN
an flow g.p.m.	
Temperature of water 60 Depth artesian flow encounteredft.	Work started 7-22-80 19 Completed 7-27-80 19
(9) CONSTRUCTION:	Data well delite.
Well seal—Material used Portland Cement	1 27 00
Well sealed from land surface to	Drilling Machine Operator's Certification: This well was constructed under my direct supervision. Materials used and information reported the supervision.
Diameter of well bore to bottom of seal 20 in,	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal	west kindertedge and heare.
Number of sacks of cement used in well sealsacks	[Signed] Date 7-28-80, 19.
How was cement grout placed?pumped	Drilling Machine Operator's License No. 345
	Water Well Contractor's Certification:
Was a drive shoe used? W yor C N. D.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? ☑ Yes ☐ No Plugs	Name Ladd Horn Well Drilling
Type of westers	(Person) firm or corporation)
COLI OI SHALA	Address Rotte 1 Box 14 Pilot Rock, OR 97868
Method of sealing strata off	[Signed] Add to
Was well gravel packed? A Yes □ No Size of gravel:	(Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 739 Date 7-28-80