	NC WESE	IVE	M	
NOTICE TO WATER WELL CONTRACTOR The original and first copy	DEC 1	1 1967	V	
of this report are to be	ELL REPORT THE		THE PERSON SHEET	· F
	F OREGON	EW/	350	21 M
within 30 days from the date ENGINE Please ty	pe or print) (100 1 100))1 4	
STATE ENGINEER, SALEM, OREGON 97310 Within 30 days from the date of well completion.	STATE ENGINE Permit	VO.	1 A T	/
(1) OWNER:		· / UN	270	1
Name Joy W. Aly ander	(11) LOCATION OF WELL: (4329)			
Addition to the transfer of th	County C/M D Till D Driller's well number			
Address () (+2 BOX 299 MI Itox Frequente				
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner			
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐	118 East of Silv Corner hence north			
If abandonment, describe material and procedure in Item 12.	102			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(10)			
Rotary Driven Domestic I Industrial Municipal	(12) WELL LOG: Diameter of well below casing / O			
Dug ☐ Bored ☐ Irrigation ☐ Test Well ☐ Other ☐	Depth drilled ft. Depth of comp			0 ft.
CASING INSTALLED: Threaded Welded	Formation: Describe color, texture, grain size and show thickness and nature of each stratu	and struc	ture of n	naterials;
CASING INSTALLED: Threaded □ Welded □ L.	with at least one entry for each change of forn	nation. Re	port each	h change "
" Diam. fromft. toft. Gage	in position of Static Water Level as drilling pr	oceeds. N	ote drilli	ng rates.
" Diam. fromft. toft. Gage	MATERIAL	From	то	swi
	Top Soil & clay	0	17	
PERFORATIONS: Perforated? Yes No.	(A	3 2000	سے وہ	
Type of perforator used Ac ctylene	Conglomerate (Brown)		35	
Size of perforations /2 in. by in.	Brown Coment Gravel	.3.5	66	
perforations from ft. to ft.	- CEMPENT GIAG	الارد	<u>vv</u>	
perforations from tt. to ft. perforations from tt. to ft. perforations from 40 ft. to 60 ft.	Some daving + water	66	70	
perforations from 70 ft. to 60 ft.				
perforations fromft. toft.	Cement Gravel (Brown)	70	102	
	- C	 		
(7) SCREENS: Well screen installed? Yes The	Some cleaner (water	4/02	105	
Manufacturer's Name	· Cement Gravel (Brown)	10.5	125	
Type Model No Diam Slot size Set from ft. to ft.	The state of the s	103		
Diam. Slot size Set from ft. to ft.	Hard Brown Clay with Mixed			
	Sand + Fine Gravel	125	157	
(8) WATER LEVEL: Completed well.				
Static level 54ft below land surface Date Oct. //	Soft brown Grayd	2	100	
esian pressure lbs. per square inch Date	Some water	157	185	
(9) WELL TESTS: Drawdown is amount water level is lowered below static level	Hard Brown Clay with mured			 •.
Was a pump test made? The tes I No If yes, by whom?	Sand - Med Fine.	185	210	<u> </u>
weld: 80 gal./min. with 75 ft. drawdown after 4 hrs.	Work started Sep. 12 19 67 Complet		11	1967
120 " 140 " 4 "	Date well drilling machine moved off of well			19
" " " "			- · · · · · ·	
Railer teet gol /win	Drilling Machine Operator's Certification: This well was constructed under my di	irect supe	rvision.	Mate-
nis,	rials used and information reported above knowledge and belief.	e are tr	ue to n	y best
		0	+ 17	17
Temperature of water 52 Was a chemical analysis made? Yes II-No	[Signed] (Drilling Machine Operator)	Date O	<u> </u>	19
(10) CONSTRUCTION: Well seal—Material used 4 Minus Concrete	Drilling Machine Operator's License No	11		· · · · · · · · · · · · · · · · · · ·
Well seal-Material used 74 Minus Concrete	The state of the s			
Septil of seal	Water Well Contractor's Certification:			
Diameter of well bore to bottom of sealin.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.			
Were any loose strata cemented off?	NAME Lowell W. Marlatt			
Did any strata contain unusable water? Yes De No	(Person, firm or corporation) (Type or print)			
	Address R.T. # 2 Box III A A	4ilton f	rec má	tes, Ore.
Type of water? depth of strata Method of sealing strata off	P II at hel			
The state of the s	[Signed] Jowell M. Mark	etr -		-
Was well gravel packed? ☐ Yes ②No Size of gravel:	1 (42)	ùt. 17	,	ب- بر
Gravel placed from ft. to ft.	Contractor's License No.	E(- / (,	19. 6. 7.