NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be

STATE ENGINEER, SALEM, OREGON 97310 Within 30 days from the date of well completion.

WATER WELL REPORTUL 1 0 1974

STATE OF OREGONSTATE ENGINEER

State Well No. 6N/35E-22

(Please type or print)

SALEM. OREGON State Permit No.

(Do not write above this line) 66882

REGEIVEL

(1) OWNER:	(10) LOCATION OF WELL:
Name Mr. & Mrs. Robert D. Schubert	County Umatilla Driller's well number
Address Rt. 2, Box 280	
Milton-Freewater, Oregon	Bearing and distance from section or subdivision corner approx.
(2) TYPE OF WORK (check):	150 feet due East from West line
New Well	of section 22.
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Double of welfall water and find a
Rotary Driven Domestic Industrial Municipal	2.6
Cable	Static level 34 ft. below land surface. Date 6/5/24
	Artesian pressure Ibs. per square inch. Date
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing
8 " Diam. from 6 ft. to 8 8 ft. Gage 27/	Depth drilled / 19 ft. Depth of completed well / 1 9 ft.
"Diam. from	
" Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,
PERFORATIONS: Perforated? W Ves. II No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used MILL 5	
3/-	MATERIAL From To SWL
Size of perforations 73 in. by in. 14.0 perforations from 4.0 ft. to 7.2 ft.	BLACK TOP Soil 0 11
perforations fromft. toft. perforations fromft. toft.	CONCLOMERATE. 30 119 34
perforations fromft. toftftft.	CONCLOMERATE, 30 119 34 CRAVEL WITH BROWN
	CLAY CWATER BEARING
(7) SCREENS: Well screen installed? Yes No	TENT CARRIED
Manufacturer's Name	
Type Model No.	
Diam. Slot size Set from ft. to ft.	
Diam. Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? 🗌 Yes 💆 No If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs.	
" " "	
" " " " " " " " " " " " " " " " " " " "	And
Bailer test 32 gal./min. with 12 ft. drawdown after/ 2 hrs.	The state of the s
Artesian flow g.p.m.	
perature of water 5 3 Depth artesian flow encounteredft.	
	Work started 6/4/ 1974 Completed 6 159 1974
(9) CONSTRUCTION:	Date well drilling machine moved off of well 6/12 1974
Well seal-Material used FORTLAND CEMENT	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision.
Diameter of well bore to bottom of seal in.	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal in.	[Signed] Raymond Hardung Date 7.3 , 1974
Number of sacks of cement used in well seal	Drilling Machine Operator)
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No. 1.5 8
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? 🕱 Yes 🗌 No Plugs Size: location ft.	true to the best of my knowledge and belief. Name HARDING DRILLING CO
Did any strata contain unusable water? 🔲 Yes 📋 No	(Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address 77350 3RD WALLAWALLA WASH
Method of sealing strata off	
Was well gravel packed? Yes No Size of gravel:	[Signed] Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No 345 Date 7/2 1974
	19.1 19.1