NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the STATE OF OREGON

WATER WELL REPORT

197

STATE OF OREGON

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date AIER RESOURCES (FDESP Type or print) of well completion. SALEM. ORECONO write above this line) State Well No. Con/356-24cd State Permit No. ..

Oracin, Oracon	- -
(1) OWNER:	(10) LOCATION OF WELL:
Name, Tillian a. Maddin of Sailard S. Welson	County Umatilla Driller's well number
Address 625 of Garl gaster Route 1 Box 24	pdG I glass out of the
Talea Waller The Bressott, Na. 9934	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	mca Laller later
New Well K Deepening Reconditioning Abandon	South of House
If abandonment, describe material and procedure in Item 12.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.
Potowy D Duisson D	Depth at which water was first found /6 ft.
Cable Jetted Domestic Industrial Municipal D	Static level ft. below land surface. Date #//8/7
Dug	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded Welded 27 "Diam. from O ft. to 90 ft. Gage 4.50 "Diam. from ft. to ft. Gage	(12) WELL LOG: Diameter of well below casing S Depth drilled \$50 ft. Depth of completed well \$150 ft. Formation: Describe color, texture, grain size and structure of materials;
	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	BLACK TOP SOIL 0 6
perforations from ft. to ft.	GRAVELY SAND 6 38
perforations from ft. to ft.	BLACK SAND 38 86
perforations from ft. to ft.	BROWNCLAY & BRAVEL 86 115
(F) CODENIC	CRAVEL WATER 115 150 6
Work bereen minuted: [] Tes M No	BEARING
Manufacturer's Name	
Type Model No.	
Diam. Slot size Set from ft. to ft. Diam. Slot size Set from ft. to ft.	
Set from the to the fit.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? Yes No If yes, by whom?	
-Field:	
feld: gal./min. with ft. drawdown after hrs.	
" " " " " " " " " " " " " " " " " " "	
Bailer test / gal./min. with & ft. drawdown after/ 2 hrs.	
Artesian flow g.p.m.	
mperature of water 3 Depth artesian flow encountered ft.	Work started 4//7 19 77 Completed 5/20 19 77
(9) CONSTRUCTION;	Date well drilling machine moved off of well 5/22 1977
Well seal-Material used JCRTLAND CEMENT	Drilling Machine Operator's Certification:
Well sealed from land surface to	This well was constructed under my direct supervision.
	Materials used and information reported above are true to my
Diameter of well bore to bottom of sealin. Diameter of well bore below sealin.	best knowledge and belief.
Number of sector of sector of	[Signed] Marine December Date & 1977
Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No. 150
Brand name of bentonite	
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:
of waterlbs./100 gals.	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? Yes 🗆 No Plugs Size: location ft.	true to the best of my knowledge and belief. Name HARDING DRILLING Co.
Did any strata contain unusable water? 🔲 Yes 🕱 No	Name TALL (Cerson, firm or corporation) (Type or print)
Type of water? depth of strata	Address RT23 NO-3RD WALLA WALLA WASH
Method of sealing strata off	P 0 1 0:
Was well gravel packed? ☐ Yes ☒ No Size of gravel:	[Signed] M. ayrnaux Math. (Water Well Contractor)
Gravel placed from ft. to ft.	A CONTRACTOR OF THE CONTRACTOR
It. WII.	Contractor's License No. 4.5 Date 6/20 , 19.7.