## NOTICE TO WATER WELL CONTRACTOR The original and first copy

of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED

WATER WELL REPORT AUG 2 3 1973 State Well No. 6N 35E-25

STATE OF OREGON STATE ENGINEER

(Please type or print) STATE ENGINEER

(Do not write above this line) SALEM, OREGON

(1) OWNER:	(10) LOCATION OF WELL:		
Name John H. McMunn	County Umatilla Driller's well nu		
Address Route L - Box 103	14 14 Section 25 T. 6N	r. 35	Ew.m.
Milton-Freewater, Oregon	Bearing and distance from section or subdivision	on corner	
(2) TYPE OF WORK (check):			11.000
New Well Deepening Reconditioning Abandon			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed we	eII.	•
(3) TYPE OF WELL: (4) PROPOSED USE (check):	20		
Determ D Determ D			
Cable Jetted D Domestic in industrial in municipal	Static level 10 ft. below land surface. Date 8/1/73		
Dug 🗌 Bored 🗍 Irrigation 🗍 Test Well 🗎 Other 🔲	Artesian pressure lbs. per square inch. Date		
(5) CASING INSTALLED: Threaded  Welded	(12) WELL LOG: Diameter of well below casing		
8 " Diam. from 0 ft. to 69 ft. Gage 280	Depth drilled 69 32 ft. Depth of completed well 69 ft.		
"Diam. from	Formation: Describe color, texture, grain size and structure of materials;		
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in		
(b) PERFORATIONS: Perforated?   Yes  No.	position of Static Water Level and indicate princ	cipal water-bearing	ig strata.
Type of perforator used	MATERIAL	From To	SWL
		0 2	-
Size of perforations in. by in.	Gray clay Sm.boulders & gray clay	2 19	
perforations fromft. toft.	Fine gravel	19 21	
perforations fromft. toft.	Sm. boulders & gray clay	21 31	
perforations from ft. to ft.	Dry medium gravel	31 32	
(7) SCREENS: Well screen installed?  Yes  No	Sm. boulders & gray clay	32 39	35
Manufacturer's Name	Coarse gravel	39 59	Jio
Type Model No.	Medium sand	59 69	LiO -
Diam. Slot size Set from ft. to ft.	NGULDIR SAIR	7, 2,	
Diam. Slot size Set fromft. toft.			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
Was a pump test made?   Yes   No If yes, by whom?			-
gal./min. with ft. drawdown after hrs.			
gair/iiiii. Wida 26. ddawdd ma daod	The second secon		
" " " " " " " " " " " " " " " " " " "			
	· Service of the serv		
Bailer test 20 gal./min. with 0 ft. drawdown after 1 hrs.	No. of the second secon		
Antesian flow g.p.m.		<u> </u>	
emperature of water 55 Depth artesian flow encountered ft.	Work started 7/23 19 73 Complete	ed 8/1	19 73
(9) CONSTRUCTION:	Date well drilling machine moved off of well	8/1	<sup>19</sup> 73
Well seal-Material used Bentonite slurry	Drilling Machine Operator's Certification:		
Well sealed from land surface to	This well was constructed under my Materials used and information reported	above are tru	vision.
Diameter of well bore to bottom of sealin.	best knowledge and belief.		. !
Diameter of well bore below sealin.	[Signed] & M. Dehrum. (Willing Machine Operator)	Date8/21	L, 1973
Number of sacks of cement used in well sealsacks			
Number of sacks of bentonite used in well seal	Drilling Machine Operator's License No.	754	
Brand name of bentonite Montana	Tileten Wall Contractor's Contification		
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:	tation and this	roport te
of water50. lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Was a drive shoe used? ★ Yes □ No Plugs Size: location ft.	Name E. M. J. Behrens  (Person, firm or corporation) (Type or print)  Address P.O. Box 201-Milton-Freewater, Oreg.		
Did any strata contain unusable water?   Yes No	(Person, firm or corporation)	(Type or pr	int)
Type of water? depth of strata	Address P.O. Box 201-Milton-I	reewater	Ureg.
Method of sealing strata off	EmaBala.		
	[Signed] EMJ Behren (Water Well Cont	ractor)	
	Contractor's License No229. Date	8/21	19.73
Gravel placed from ft. to ft.	1 COMMISSION DE LECTION TION MINISTER, DANG MINISTER		,